

SOURCEWELL CONTRACT NO. 101221-GPV

GapVax®



PREPARED BY

WECO INDUSTRIES

Noah Johnson - noahjohnson@wecoind.com

PREPARED FOR

Freddy Barajas

City of San Leandro
3000 Davis Street
San Leandro, CA 94577

QUOTE

GapVax®



QUOTE ID
52125

UPDATED:
2/25/2025



2025 MC1005-3S4X COMBINATION JET/VAC

QUOTE ID: 52125

May 20, 2025

NOTE: THE GAPVAX MC UNIT MAY EXCEED FEDERAL BRIDGE ALLOWABLE WEIGHTS WHEN LOADED WITH WATER, OR DEBRIS, AND/OR BOTH WATER AND DEBRIS COMBINED. PLEASE CONSULT FACTORY.

	OPTION DESCRIPTION	NOTES	QTY
	CHASSIS OPTIONS		
CHA001	PETERBILT 548 (4 X 2) - 360 HP - 50,000 LB. GVWR - AUTO	MODEL YEAR 2025	1
	PACCAR PX-9 RATED FOR 360 HP	CONSULT FACTORY	
	ALLISON 6 SPEED AUTOMATIC	PRICES MAY VARY	
	20,000 LB FRONT AXLE		
	30,000 LB REAR AXLE		
	WHITE CAB COLOR		
NOTE:	DUE TO THE 2025 CARB ACT REGULATIONS, GAPVAX DOES NOT HAVE APPROVED 2026 MODEL YEAR		
NOTE:	CHASSIS FOR THESE SIX STATES: CA, OR, WA, MA, NJ, or NY, THEY MUST BE SUPPLIED LOCALLY		
	STOCK CHASSIS ARE SUBJECT TO PRIOR SALE, LIMITED QUANTITY ARE AVAILABLE		
	DEBRIS BODY OPTIONS		
STD	5 USABLE YARD DEBRIS TANK MADE OF 3/16" ASTM A-572 GRADE 50 EXTEN STEEL		STANDARD
STD	FULL-OPENING REAR TAILGATE		STANDARD
STD	STAINLESS STEEL TAILGATE SEALING ROD		STANDARD
STD	FOUR HYDRAULIC REAR DOOR LOCKS		STANDARD
STD	DUAL TAILGATE LIFT CYLINDERS		STANDARD
STD	FRONT MOUNTED HOIST CYLINDER, POWER UP AND DOWN, 55,000 LB CAPACITY		STANDARD
STD	THREE TIE-OFF ANCHORS ON TOP OF BODY		STANDARD
STD	FIVE YEAR WARRANTY ON DEBRIS TANK AGAINST RUST THROUGH, DISTORTION AND CRACKS		STANDARD
STD	THREE TIE-OFF ANCHORS ON TOP OF THE BODY 6' APART		STANDARD
	FLUSHOUT SYSTEM (CHOOSE ONE OR LESS)		
A1C	STAINLESS DEBRIS BODY FLUSH OUT SYSTEM, MOUNTED AT MID-LEVEL IN DEBRIS TANK	INCLUDES LOW POINT DRAIN	1
	6" DECANT AT BOTTOM OF TAILGATE (CHOOSE ONE)		
A2A	DRAIN AT BOTTOM OF TAILGATE - 6" BRASS LEVER VALVE WITH 15' OF LAYFLAT HOSE	VALVE IS NOT 100% LEAK PROOF	
A2B	DRAIN AT BOTTOM OF TAILGATE - 6" BUTTERFLY VALVE WITH 15' OF LAYFLAT HOSE	VALVE IS NOT REPAIRABLE	
A2C	DRAIN AT BOTTOM OF TAILGATE - 6" BRASS KNIFE VALVE WITH PNEUMATIC ACTUATOR	VALVE IS NOT 100% LEAK PROOF	

A2DB	DRAIN AT BOTTOM OF TAILGATE - 6" SS RESILIENT SEAT KNIFE VALVE WITH PNEUMATIC ACTUATOR	SEAL IS REPLACABLE	
	6" DECANT HALF WAY UP THE TAILGATE (CHOOSE ONE OR LESS)		
A24A	DECANT HALF WAY UP TAILGATE - 6" BRASS LEVER VALVE WITH HANDLE		1
A24B	DECANT HALF WAY UP TAILGATE - 6" BRASS KNIFE VALVE WITH PNEUMATIC ACTUATOR		
	4" DECANT HALF WAY UP THE TAILGATE (CHOOSE ONE OR LESS)		
A24P	DECANT HALF WAY UP TAILGATE - 4" BRASS LEVER VALVE AND ALUMINUM CAMLOCK		
A24Q	DECANT HALF WAY UP TAILGATE - 4" BRASS KNIFE VALVE WITH CYLINDER STYLE PNEUMATIC ACTUATOR		
	DEBRIS LEVEL INDICATOR (CHOOSE ONE OR MORE)		
A3	FLOAT TYPE LIQUID LEVEL INDICATOR ON TAILGATE		
A3-CS	FLOAT TYPE LIQUID LEVEL INDICATOR ON SIDE OF DEBRIS TANK		1
	PUMP OFF SYSTEM (CHOOSE ONE OR LESS)		
A5	TRASH PUMP - 3" RATED UP TO 450 GPM WITH LAY-FLAT HOSE AND CAM-LOC FITTINGS	NOT RECOMMENDED FOR CONTINUOUS USE	
A6A	TRASH PUMP - 4" RATED UP TO 800 GPM WITH LAY-FLAT HOSE AND CAM-LOC FITTINGS	NOT RECOMMENDED FOR CONTINUOUS USE	
A6AX	TRASH PUMP - SETUP ONLY	PUMP NOT INCLUDED	
A6C	SLUDGE PUMP - 4" HYDRATECH S4T (REQUIRES HYDRAULIC OIL COOLER (OPTION J303))	INCLUDES SILICONE CARBIDE SEALS FOR ABRASIVE FLUID	
A6CX	SLUDGE PUMP - SET UP ONLY FOR 4" HYDRATECH S4T (REQUIRES HYDRAULIC OIL COOLER (OPTION J303)) - SETUP ONLY	PUMP NOT INCLUDED	
	FILTER SCREENS (CHOOSE ONE PER VALVE)		
A11A	FILTER SCREEN FOR DRAIN VALVE (SHORT BOX)	REQUIRES A2	1
A11B	FILTER SCREEN FOR PUMP OFF SYSTEM (SHORT BOX)	REQUIRES A5 OR A6	
A12A	FILTER SCREEN FOR DRAIN VALVE (LONG BOX)	REQUIRES A2	
A12B	FILTER SCREEN FOR PUMP OFF SYSTEM (LONG BOX)	REQUIRES A5 OR A6	
A24E	FILTER SCREEN FOR 6" OR 4" DECANT VALVE HALF WAY UP THE TAILGATE	REQUIRES A24	
	DEBRIS BODY UPGRADES		
A17	UPGRADE TO STAINLESS STEEL DEBRIS TANK		
A20	UPGRADE TO 1/4" DEBRIS TANK		1
A20	UPGRADE TO 1/4" DEBRIS TANK	REQUIRED FOR OPTION C17	
	LADDERS (CHOOSE NONE OR BOTH)		
A21	CURBSIDE LADDER TO PORT INSPECTION AREA		1
A21B	ADD FOLDING LADDER EXTENSION	REQUIRES A21	1
A21X	MOUNTING TABS FOR CURBSIDE LADDER		
	OTHER OPTIONS		
A18	PURGE VALVE AT GRAVITY DRAIN (1-1/4" BALL VALVE)		1
A22A	GALVANIZED BOLT ON TAILGATE SPLASH SHIELDS		
A22B	STAINLESS STEEL BOLT-ON TAILGATE SPLASH SHIELD		1
A23	ELECTRIC VIBRATOR FOR DEBRIS TANK	REQUIRES OPTION A20	

A34B	UPGRADE DEBRIS BODY BAFFLE TO STAINLESS STEEL	
A34B	UPGRADE DEBRIS BODY BAFFLE TO STAINLESS STEEL	SS DEBRIS BODY UPGRADE
A37A	UPGRADE BODY INLET CANNON TO HX STYLE WITH CLEANOUT	1
A39	LONG POLE HOLDER TO ACCOMMODATE (3) 12' CLAM DIGGERS	
A44	PNEUMATIC TAILGATE PROP (IN ADDITION TO STANDARD TAILGATE PROP ROD)	1
WATER TANK OPTIONS		
STD	1000 GALLON WATER TANK MADE OF 3/16" 304 STAINLESS STEEL	STANDARD
STD	4" HIGH ANTI-SIPHON RING WITH (4) 2-1/2" HOLES	STANDARD
STD	WATER TANK LEVEL SIGHT TUBE ON CURBSIDE	STANDARD
STD	DRAIN VALVE AT BOTTOM OF WATER TANK	STANDARD
STD	3" FILL LINE WITH 2-1/2" FIRE HOSE CONNECTION CURBSIDE	STANDARD
STD	3" WATER STRAINER WITH STAINLESS STEEL SCREEN ON WATER TANK FILL LINE	STANDARD
STD	3" SUPPLY LINE TO WATER PUMP MOUNTED AT REAR HINGE PIN	STANDARD
STD	FIVE YEAR WARRANTY ON WATER TANK AGAINST RUST THROUGH, DISTORTION AND CRACKS	STANDARD
B2	AUTOMATIC WATER TANK FILL SYSTEM	
B3	TANK INTER-CONNECT WITH DEBRIS TANK	REQUIRES A2, B10
B6	EXTRA SIGHT TUBE ON DRIVER'S SIDE	1
B7a	UPGRADE WATER TANK TO 1/4" STAINLESS STEEL	
B10	ADDITIONAL 3" FILTER BETWEEN WATER TANK AND PUMP (3" Y-STRAINER)	1
B11	ADDITIONAL 3" WATER LINE FILL ON DRIVER'S SIDE	CONSULT ENGINEERING
B20	UPGRADE MANWAY, ANTI-SIPHON, AND WELD IN FITTINGS TO STAINLESS STEEL	
B23A	GALVANIZED BAFFLES IN THE WATER TANK	
B23B	STAINLESS BAFFLES IN THE WATER TANK	1
B24	30" BAG FILTER UPGRADE WITH STAINLESS HOUSING ON WATER TANK FILL LINE	1
B25	INSTALL CUSTOMER SUPPLIED WATER METER - MUST BE SHIPPED TO GAPVAX PRIOR TO ENGINEERING REVIEW OF ORDER	CONSULT ENGINEERING
B30	UPGRADE TO BUTTERFLY VALVE IN 3" SUPPLY LINE	STANDARD
VACUUM SYSTEM OPTIONS		
STD	TRUE 8" DIAMETER VACUUM SYSTEM	STANDARD
STD	ROOTS TYPE VACUUM PUMP 3,500 CFM AND 16" HG	(3) 16" Hg VACUUM RELIEF VALVES
STD	VACUUM PUMP DRIVEN VIA MID-SHIP MOUNTED SPLIT SHAFT TRANSFER CASE GEARBOX	(PTO)
STD	NOISE & VIBRATION DAMPENING MOUNTS ON VACUUM PUMP AND TRANSFER CASE	STANDARD
STD	NOISE ATTENUATED VACUUM PUMP DISCHARGE SILENCER WITH RAIN CAP AND DRAIN	STANDARD
STD	24" CENTRIFUGAL CYCLONE SEPARATOR WITH 20" CHAMBER	STANDARD
STD	DUAL STAINLESS STEEL SHUTOFF FLOAT BALLS MOUNTED AT THE REAR OF DEBRIS TANK	STANDARD
STD	STAINLESS STEEL VEE-WIRE SAFETY SCREEN	STANDARD

STD	6" SAFETY VACUUM RELIEF		STANDARD
STD	PANIC SWITCH FUNCTION FOR VACUUM		STANDARD
C7	UPGRADE TO ROOTS TYPE VACUUM PUMP 4,500 CFM AND 16" HG	(4) 16" Hg VACUUM RELIEF VALVES	
C8	UPGRADE TO ROOTS TYPE VACUUM PUMP 4,500 CFM AND 18" HG	(4) 18" Hg VACUUM RELIEF VALVES	1
C17	UPGRADE TO HIBON 840 VACUUM PUMP 3,850 CFM AND 27" HG	REQUIRES OPTIONS A20 AND C18	
	OTHER OPTIONS		
C2	6" MANUAL VACUUM RELIEF VALVE	RECOMMENDED WITH PUMP-OFF SYSTEM	1
C5AC	UPGRADE CYCLONE AND FINAL FILTER HOUSING TO STAINLESS STEEL	VACUUM RELIEF VALVE DUCT REMAINS CARBON STEEL	
C18	VULKAN VIBRATION DAMPENING BLOWER COUPLER		
C18	VULKAN VIBRATION DAMPENING BLOWER COUPLER	REQUIRED FOR OPTION C17	
C19	UPGRADE TO XL TRANSFER CASE	9-LITER ENGINE = UP TO 5300 CFM, REQUIRES OPTION C8	1
C20	5-YEAR NON-PRORATED VACUUM PUMP (BLOWER) WARRANTY AGAINST DEFECTS IN MATERIALS AND WORKMANSHIP		
C21	5-YEAR NON-PRORATED TRANSFER CASE WARRANTY AGAINST DEFECTS IN MATERIALS AND WORKMANSHIP		
	NOTE: NEITHER THE VACUUM PUMP (BLOWER) OR TRANSFER CASE EXTENDED WARRANTY COVER ANY DAMAGE DUE TO MISUSE (SUCH AS WATER DAMAGE, FROZEN WATER, DIRT, RUST, ETC. IN THE VACUUM PUMP), REQUIRES PROOF OF COMPLETED OIL CHANGES PER THE INTERVAL MAINTENANCE CHART POSTED ON THE UNIT OR IN THE MANUAL. SHIPPING IS NOT INCLUDED. THESE WARRANTIES ARE ONLY AVAILABLE FOR MUNICIPAL OWNED UNITS ONLY.		
	WATER SYSTEM OPTIONS		
STD	SHAFT-DRIVEN WATER PUMP RATED FOR 80 GPM AND 2,000 PSI		
STD	TRI-PLEX WATER PUMP SYSTEM		STANDARD
STD	AIR PURGE SYSTEM FOR PRIMARY CIRCUIT		STANDARD
STD	LOW POINT DRAIN VALVES ON WATER LINES		STANDARD
D4	MULTIFLOW CONTROL AND SAFETY REGULATOR VALVE (MSUV)		1
	STANDARD WASHDOWN CIRCUIT OPTIONS		
D39	REMOVE STANDARD WASHDOWN CIRCUIT		
STD	WASHDOWN CIRCUIT WITH 50' X 1/2" HOSE, QUICK CONNECT, AND WASHDOWN HAND GUN	50-FT HOSE REEL	STANDARD
STD	WASHDOWN CIRCUIT(S) WILL INCLUDE A SAFETY FLOW RESTRICTOR (1/4" HOSE)		STANDARD
D7A	HOSE REEL FOR STANDARD WASHDOWN CIRCUIT, 50' X 1/2"		1
D25A	HOSE REEL FOR STANDARD WASHDOWN CIRCUIT, 100' X 1/2"		
	TRI-PLEX JETTER PUMP (CHOOSE ONE)		
D1A	GIANT GP8000 SERIES WATER PUMP RATED 80 GPM @ 2,000 PSI	(P/N: PUM022794)	
D1B	GENERAL MKS "2" SERIES WATER PUMP RATED AT 80 GPM @ 2000 PSI	(P/N: PUM022755)	
D3A	GIANT GP8000 SERIES WATER PUMP RATED 80 GPM @ 2,500 PSI	(P/N: PUM022794)	
D3B	GENERAL MKS "2" SERIES WATER PUMP RATED AT 80 GPM @ 2500 PSI	(P/N: PUM022755)	
D5A	GIANT GP8000 SERIES WATER PUMP RATED AT 63 GPM @ 3000 PSI	(P/N: PUM022800)	1

D5B	GENERAL MKS "2" SERIES WATER PUMP RATED AT 63 GPM @ 3000 PSI	(P/N: PUM022792)	
D24A	GIANT WATER PUMP RATED AT 100 GPM @ 2000 PSI WITH 1-1/4" PLUMBING	(P/N: PUM022801)	
D24B-100	GENERAL MKS "2" SERIES WATER PUMP RATED AT 100 GPM @ 2000 PSI WITH 1-1/4" PLUMBING	(P/N: PUM022765)	
D24B-120	GENERAL MKS "2" SERIES WATER PUMP RATED AT 120 GPM @ 2000 PSI WITH 1-1/4" PLUMBING	(P/N: PUM022750)	
DWSL	DUAL 3" WATER SUPPLY LINE UPGRADE REQUIRED FOR 100 GPM WATER SYSTEM	REQUIRED FOR OPTION D24A/B	
D-GPVC	VIBRATION DAMPENING COUPLER - WATER PUMP		REQUIRED
	JETTER WATER SYSTEM OPTIONS		
D4-GUARD	STAINLESS BRANCH GUARD (P/N: F017493-SS) FOR THE MULTIFLOW CONTROL AND SAFETY REGULATOR VALVE (MSUV)		
D8	ADDITIONAL JETTER WATER SYSTEM CIRCUIT CONNECTION WITH 50' X 1/2" HOSE, QUICK CONNECT (WILL INCLUDE A SAFETY FLOW RESTRICTOR (1/4" HOSE))	HOSE REEL NOT INCLUDED	
D8B	ADDITIONAL JETTER WATER SYSTEM CIRCUIT CONNECTION WITH ADJUSTABLE PRESSURE REGULATOR, PRESSURE GAUGE, AND 50' X 1/2" HOSE, QUICK CONNECT (FOR HX HANDGUN)	PRESSURE REG. REPLACES FLOW RES., HOSE REEL NOT INCLUDED	
D7C	HOSE REEL FOR ADDITIONAL JETTER WATER SYSTEM CIRCUIT, 50' X 1/2"	LOCATION: FRONT OF TRUCK BUMPER	1
D25C	HOSE REEL FOR ADDITIONAL JETTER WATER SYSTEM CIRCUIT, 100' X 1/2"	LOCATION? (FRONT OR MID CURB SIDE)	
D16	1-1/4" HIGH PRESSURE PLUMBING TO FRONT HOSE REEL		
D16	1-1/4" HIGH PRESSURE PLUMBING TO FRONT HOSE REEL	REQUIRED FOR OPTION D24A/B	
D20A	NON-REMOVABLE LATERAL HOSE REEL - 150' X 1/2" HOSE		
D20B	REMOVABLE LATERAL HOSE REEL - 150' X 1/2" HOSE		
D21	WATER RECIRCULATION VIA AUTOMATIC TRANSMISSION (INCLUDES WASHDOWN, ADDITIONAL CIRCUITS, AND LATERAL REEL)	JETTER SYSTEM ONLY	1
D21A	1-1/4" WATER RECIRCULATION SYSTEM VIA AUTOMATIC TRANSMISSION (INCLUDES WASHDOWN, ADDITIONAL CIRCUITS, AND LATERAL REEL)		
D28A	GLYCOL INJECTION SYSTEM - JETTER PUMP ONLY		
	HYDRO EXCAVATING (HX) SYSTEM (CHOOSE ONE OR LESS)	GUN & REEL NOT INCLUDED	
D307HM	14 GPM / 4,000 PSI (GIANT LP301), POWERED VIA TRANSFER CASE DRIVEN INDEPENDENT HYDRAULIC SYSTEM (FIXED SPEED HYDRAULIC CONTROL)	REQUIRES OPTION J303A DUAL HYDRAULIC OIL COOLERS	
D301HA	13 GPM / 3,000 PSI GIANT P420HP, POWERED VIA AUTOMATIC TRANSMISSION DRIVEN INDEPENDENT GEAR PUMP HYDRAULIC SYSTEM (FIXED SPEED HYDRAULIC CONTROL) (PLEASE SELECT OPTION D21-MCHX TO ADD COLD WEATHER WATER RE-CIRCULATION)	REQUIRES OPTION J303 AND OPTION G2B-SI (MODE 3), REQUIRES ENGINEERING APPROVAL	
D301HM	13 GPM / 3,000 PSI HX WATER SYSTEM POWERED VIA TRANSFER CASE DRIVEN INDEPENDENT HYDRAULIC SYSTEM	REQUIRES OPTION J303 HYDRAULIC OIL COOLER	
D27A	10 GPM / 2,500 PSI HYDRAULICALLY DRIVEN PUMP (COMMON WITH BODY HYDRAULIC SYSTEM)	REQUIRES OPTION J303 HYDRAULIC OIL COOLER	
D27XB	PROVISIONS TO ADD THE "OPTION D27A" SERIES HX PACKAGE, ADDED HYD VALVE SECTION, UPGRADE HYDRAULIC PUMP TO 75CC, 2" OIL SUCTION LINE, PORT FOR HX WATER SUPPLY AND RETURN, PLUG-IN PORT (ONLY) FOR G2B HX CONTROL ELECTRICAL	REQUIRES OPTION J303 HYDRAULIC OIL COOLER	
	HX WATER SYSTEM OPTIONS (CONSULT ENGINEERING)	(N/A FOR JETTER PUMP)	
D4-HX+RA	PNEUMATICALLY OPERATED HX WATER PRESSURE RELIEF VALVE WITH ACTUATED HOSE REEL VALVE (P/N: VAL022790) (G2B)	HX SYSTEM	
D7B	50' X 1/2" HOSE REEL FOR HX SYSTEM		

D25B	100' X 1/2" HOSE GUN REEL FOR HX SYSTEM	
D25B-PM	100' X 1/2" HOSE REEL FOR HX SYSTEM WITH HD AIR MOTOR RETRACT AND PUSH LEVER AIR CONTROL	WILL NOT FIT IN THE 48" PUMP ENCLOSURE
D18	AIR OUT FOR HX SYSTEM / HX CIRCUIT	
D28	GLYCOL INJECTION SYSTEM - HX SYSTEM	
	NOTE: IF GLYCOL IS SELECTED FOR BOTH THE JETTER SYSTEM (OPTION D28A) AND THE HX SYSTEM (OPTION D28B), ONLY ONE COMMON GLYCOL TANK WILL BE PROVIDED	
D30D	STAINLESS BOX 60" WIDE X 28" DEEP X 24" TALL PUMP ENCLOSURE FOR HX PUMP, REEL, & REGULATOR	
D30B	STAINLESS BOX 48" WIDE X 28" DEEP X 24" TALL PUMP ENCLOSURE HX PUMP, REEL, & REGULATOR	
D372A	ADD HEATER TO OPTION D30 PUMP ENCLOSURE - VIA ENGINE COOLANT SYSTEM (CHASSIS MUST HAVE FACTORY COOLANT LINES PROVIDED AT BACK OF CAB)	REQUIRES OPTION D30
D21-MCHX	HX SYSTEM COLD WEATHER RECIRCULATION - VIA AUTOMATIC TRANSMISSION (CONSULT ENGINEERING - WILL ONLY FIT ON SELECT TRUCKS - REQUIRES 2ND TRANSMISSION PTO WINDOW TO BE USEABLE)	
D29F-MC	COMPLETE 420,000 BTU (EPPS) BURNER SYSTEM (P/N: ACC022942) AND MOUNTING ON MID-CURBSIDE OF UNIT, INCLUDES ENCLOSED CABINET (4,000 PSI RATED)	
D34	MOUNTS ONLY FOR OPTION D29F-MC (VERTICAL BURNER) OR VERTICAL TOOL BOX ON MID-CURBSIDE OF UNIT	
D34	MOUNTS ONLY FOR OPTION D29F-MC (VERTICAL BURNER) OR VERTICAL TOOL BOX ON MID-CURBSIDE OF UNIT	
	HX SHUT-OFF GUNS AND LANCES	
D35	1/4" HX LANCE WITH 5' EXTENSION AND TURBO NOZZLE	
D35A	1/2" HX LANCE WITH 6' EXTENSION AND TURBO NOZZLE	
D35B	1/2" HX LANCE WITH 6' EXTENSION AND RIPSAW NOZZLE	
D35C	1/2" "DIG PIG" HX LANCE WITH 6' EXTENSION AND "DIG PIG" HX NOZZLE	
D35D	3/8" HX LANCE WITH 6' EXTENSION AND TURBO NOZZLE	
D35E	3/8" HX LANCE WITH 6' EXTENSION AND RIPSAW NOZZLE	
D36A	1/2" X 3' LANCE EXTENSION WITH QUICK CONNECTS (CAT022385)	
D36B	1/2" X 5' LANCE EXTENSION WITH QUICK CONNECTS (CAT022386)	
D36C	3/8" X 3' LANCE EXTENSION WITH QUICK CONNECTS (CAT022387)	
D36D	3/8" X 5' LANCE EXTENSION WITH QUICK CONNECTS (CAT022388)	
BOOM OPTIONS		
STD	8" FRONT MOUNTED TELESCOPING BOOM WITH 26' REACH AND 180 DEG. ROTATION	STANDARD
STD	180 DEGREE POWER ROTATION VIA WORM DRIVE	STANDARD
STD	DUAL 4" LIFT CYLINDERS	STANDARD
STD	CAB PROTECTION RACK	STANDARD
E6	REMOTE LUBE FOR BOOM LIFT AND ROTATION	1
E7	3/16" HEAVY DUTY BOOM ELBOW WITH 6" FORMED CHANNEL RADIUS	1
E7A	3/16" HEAVY DUTY BOOM ELBOW WITH HARDENED CARBIDE LINER (P/N: TEX012642)	
HOSE REEL OPTIONS		

STD	FRONT FRAME MOUNTED HOSE REEL WITH 180 DEGREE ARTICULATION	STANDARD
STD	HOSE REEL RATED FOR 800' OF HOSE AND 3,000 PSI	STANDARD
STD	EXTERIOR HOSE EXPANSION RIBS	STANDARD
F1A	FOOTAGE COUNTER ON SIDE OF SPOOL	1
F1C	DIGITAL FOOTAGE COUNTER - SHAFT-MOUNTED	1
F6	UPGRADE FRONT HOSE REEL TO POWER ARTICULATE VIA HYDRAULICS	1
F11	AUTOMATIC HOSE LEVEL WINDER (INCLUDES "J-HOOK" STLYE HOSE GUIDE)	
F16	DOUBLE ROLLER UPGRADE ON MANUAL LEVEL WIND	1
F16A	DOUBLE ROLLER UPGRADE ON AUTO LEVEL WIND	
F17	HOSE TENSIONER	CONSULT ENGINEERING
CONTROLS, GAUGES, ACCESSORIES OPTIONS		
STD	CAB-MOUNTED CONTROLS FOR BLOWER AND HYDRAULICS	STANDARD
STD	CONTROL PANEL MOUNTED AT FRONT HOSE REEL WITH WATER PUMP CONTROLS	STANDARD
STD	OPERATOR CONTROL PANEL INCLUDES GAUGES FOR ENGINE, HYDRAULICS, VACUUM, AND WATER PUMP	STANDARD
STD	PANIC SWITCH TO RELIEVE WATER PRESSURE AND VACUUM ON FRONT PANEL AND CURB SIDE OF UNIT	STANDARD
G0	INTERNATIONAL DIAMOND LOGIC CONTROLS SYSTEM	CONSULT ENGINEERING, REQUIRES NAVISTAR CHASSIS
LOW WATER PROTECTION (CHOOSE ONE OR LESS)		
G2B	G2B CONTROL SYSTEM WITH DM430 DISPLAY INCLUDES:	WIRELESS CONTROL REQUIRED
G2B-SI	G2B-SI CONTROL SYSTEM WITH DM430 DISPLAY INCLUDES:	WIRELESS CONTROL REQUIRED
G2E SYSTEM (INCLUDES WIRELESS)		
G2E	G2E CONTROL SYSTEM WITH 7" DISPLAY MODULE INCLUDES:	
G2E-CAB	CAB MOUNTED DISPLAY MODULE FOR G2E SYSTEM ENGAGEMENTS AND CONTROLS	G2E CAB DISPLAY
	LOW WATER SHUTDOWN PROTECTION	1
	HIGH WATER TEMPERATURE SHUTDOWN PROTECTION	1
	ENGINE OVERSPEED PROTECTION	1
	ON-SCREEN DIAGNOSTICS FOR WATER, PTO AND ENGINE LEVELS	1
	TEMPERATURE AND PRESSURE LEVELS FOR VACUUM, WATER, HYDRAULICS	
	PROVISION FOR INCLUDING DIGITAL FOOTAGE COUNTER ON SCREEN	F1C NOT INCLUDED
	E-STOP FOR WATER VACUUM AND HYDRAULICS	
	TRANSMISSION CONTROL FOR SHIFTING OUTSIDE OF THE CAB	
	WIRELESS CONTROL SYSTEM	OPTION G2E INCLUDES THIS WIRELESS SYSTEM
	HOSE SPOOL IN/OUT WITH SPEED CONTROL	
	FRONT HOSE REEL WATER ON/OFF, PRESSURE ON/OFF	
NOTE:	WIRELESS TO INCLUDE HX WATER PRESSURE (ON/OFF) CONTROL	

	G2E OPTIONS, CONSULT ENGINEERING		
	INDICATORS AND GAUGES (CHOOSE ANY)		
G4A	HIGH DEBRIS LEVEL LIGHT & ALARM WIRED TO VACUUM RELIEF	REQUIRES A3	1
G6	BLOWER TEMPERATURE GAUGE WIRED TO VACUUM RELIEF		1
G14	BODY UP WARNING		1
G15	TAILGATE UP WARNING		1
G16	BOOM UP WARNING		1
	REMOTES (CHOOSE ONE OR LESS WIRELESSS)		
G19	WIRELESS REMOTE WITH BOOM, VACUUM, AND WATER PRESSURE FUNCTIONS	STANDARD	1
G19			
NOTE:	WIRELESS TO INCLUDE HX WATER PRESSURE (ON/OFF) CONTROL		
G21D	WIRELESS REMOTE WITH BOOM, VACUUM, FRONT HOSE REEL WATER ON/OFF, AND FRONT HOSE REEL IN/OUT (HOSE REEL ROTATE INCLUDED ONLY IF OPTION F6 IS SELECTED)	INCLUDES HOSE REEL LEFT/RIGHT	
G21E	WIRELESS REMOTE WITH BOOM, VACUUM, FRONT HOSE REEL WATER ON/OFF, HOSE REEL IN/OUT, AND REMOTE BODY DUMP CONTROLS (HOSE REEL ROTATE INCLUDED ONLY IF OPTION F6 IS SELECTED)	INCLUDES HOSE REEL LEFT/RIGHT	
G21F	WIRELESS REMOTE WITH BOOM, VACUUM, WATER PRESSURE, AND REMOTE BODY DUMP CONTROLS		
	WIRELESS TYPE		
G21-TD	AARCOMM TRIDENT REMOTE		1
G21-AWR	ADDITIONAL WIRELESS TRANSMITTER		1
	OTHER OPTIONS		
G30	ADDITIONAL ELECTRICAL SWITCH ON CONTROL PANEL	SWITCH FOR ? PLEASE IDENTIFY FUNCTION	
G30-FHR	ADD SWITCH ON CAB CONSOLE FOR FRONT HOSE REEL ARTICULATE (LEFT/RIGHT)	REQUIRES OPTION F6	1
	LIGHTING		
STD	TRUCK-LITE LED RUNNING (MARKER) LIGHTS		STANDARD
STD	LED STOP/TAIL/TURN LIGHT WITH POLISHED STAINLESS STEEL BOXES		STANDARD
	FRONT STROBE LIGHT (CHOOSE ONE OR LESS)		
H1	ONE LED STROBE BEACON LIGHT - FRONT (SAE CLASS-1 (SAE J595) COMPLIANT)	(WHELEN L10 OR EQUAL)	
H1B	TWO (2) LED STROBE BEACON LIGHT - FRONT (SAE CLASS-1 (SAE J595) COMPLIANT)	(WHELEN L10 OR EQUAL)	1

H1C	ONE LED STROBE BEACON LIGHT - FRONT (CALIFORNIA TITLE-13 COMPLIANT)	(HELLA K-LED 100 LED OR EQUAL) (P/N: LHT022550)	
H1D	TWO (2) LED STROBE BEACON LIGHT - FRONT (CALIFORNIA TITLE-13 COMPLIANT)	(HELLA K-LED 100 LED OR EQUAL) (P/N: LHT022550)	
	REAR STROBE LIGHT (CHOOSE ONE OR LESS)		
H2	ONE LED STROBE BEACON LIGHT - REAR (SAE CLASS-1 (SAE J595) COMPLIANT)	(WHELEN L10 OR EQUAL)	
H2B	TWO (2) LED STROBE BEACON LIGHT - REAR (SAE CLASS-1 (SAE J595) COMPLIANT)	(WHELEN L10 OR EQUAL)	1
H2C	ONE LED STROBE BEACON LIGHT - REAR (CALIFORNIA TITLE-13 COMPLIANT)	(HELLA K-LED 100 LED OR EQUAL) (P/N: LHT022550)	
H2D	TWO (2) LED STROBE BEACON LIGHT - REAR (CALIFORNIA TITLE-13 COMPLIANT)	(HELLA K-LED 100 LED OR EQUAL) (P/N: LHT022550)	
	BOOM WORK LIGHTS (CHOOSE ONE OR LESS)		
H5B	(2) BOOM WORK LIGHTS - HELLA LED WORK LIGHTS (PN: LHT022429)		1
H5C	(2) BOOM WORK LIGHTS - HIGH INTENSITY HELLA PB1500 LED WORK LIGHTS (PN: LHT022406)	POWER BEAM / SPOT LIGHT (RATED 1300 LUMEN EACH)	
	REAR WORK LIGHTS (CHOOSE ONE OR LESS)		
H6B	(2) REAR WORK LIGHTS - HELLA LED WORK LIGHTS (PN: LHT022429)		
H6C	(2) REAR WORK LIGHTS - HIGH INTENSITY HELLA PB1500 LED WORK LIGHTS (PN: LHT022406)	POWER BEAM / SPOT LIGHT (RATED 1300 LUMEN EACH)	
	SIDE WORK LIGHTS (CHOOSE ONE OR LESS)		
H7BA	(2) SIDE WORK LIGHTS - HELLA LED WORK LIGHTS (PN: LHT022429) (1 PER SIDE)		
H7BC	(4) SIDE WORK LIGHTS - HELLA LED WORK LIGHTS (PN: LHT022429) (2 PER SIDE)		1
H7CA	(2) SIDE WORK LIGHTS - HIGH INTENSITY HELLA PB1500 LED WORK LIGHTS (PN:LHT022406) (1 PER SIDE)	POWER BEAM / SPOT LIGHT (RATED 1300 LUMEN EACH)	
H7CC	(4) SIDE WORK LIGHTS - HIGH INTENSITY HELLA PB1500 LED WORK LIGHTS (PN:LHT022406) (2 PER SIDE)	POWER BEAM / SPOT LIGHT (RATED 1300 LUMEN EACH)	
	HAND SPOTLIGHT (CHOOSE ONE OR LESS)		
H38	CORDLESS RECHARABLE LED LIGHT		1
	FLASHERS (CHOOSE ONE OR LESS H15)		
H15	WHELEN ION SUPER LED FLASHERS - 16 LIGHT HEADS		
	2 ON EACH SIDE FRONT @ 90 DEGREES, 2 ON EACH SIDE MIDDLE @ 45 DEGREES, 4 ON EACH SIDE REAR (2 @ 45 DEGREES)		
H15A	WHELEN ION SUPER LED FLASHERS - 14 LIGHT HEADS		
	2 ON EACH SIDE FRONT @ 90 DEGREES, 2 ON EACH SIDE MIDDLE @ 45 DEGREES, 3 ON EACH SIDE REAR (1 @ 45 DEGREES)		
H15B	WHELEN ION SUPER LED FLASHERS - 12 LIGHT HEADS		1
	2 ON EACH SIDE FRONT @ 90 DEGREES, 2 ON EACH SIDE MIDDLE @ 45 DEGREES, 2 ON EACH SIDE REAR (1 @ 45 DEGREES)		1
H15C	WHELEN ION SUPER LED FLASHERS - 8 LIGHT HEADS		
	2 ON EACH SIDE FRONT @ 90 DEGREES, 2 ON EACH SIDE REAR		
H18C	REAR WHELEN ION SUPER LED FLASHERS - 6 LIGHT HEADS		
	3 ON EACH SIDE REAR (1 @ 45 DEGREES)		
	REAR ARROW LIGHT (CHOOSE ONE OR LESS)		
H17	REAR ARROW LIGHT - LED 72" WIDE - WHELEN TA45B72		
H22	REAR ARROW LIGHT - LOW PROFILE LED ARROW STICK (CLASS-1 (SAE J595))	WHELEN TAM85 OR EQUAL	1
H33	REAR ARROW LIGHT - LOW PROFILE LED (CA TITLE-13 COMPLIANT) TRAFFIC ADVISOR	(LHT022544, CODE 3 TORUS NARROWSTIK OR EQUAL)	

H36	REAR ARROW LIGHT - LED 30" X 60" TRAFCON MB315		
H40	REAR ARROW - LED - WHELEN TRAFFIC ADVISOR MODEL TA166AL5 (36" X 72")	CONSULT ENGINEERING (LHT022419)	
	CAB LIGHT BAR (CHOOSE ONE OR LESS)		
H20	CAB LIGHT BAR - LED 69" CODE 3 MODEL 21TRPL WITH FRONT TRAFFIC ADVISOR	LOW-PROFILE	
	OTHER OPTIONS		
H39A	ONE HIGH INTENSITY LED WORK LIGHT (HELLA PB1500) ON FRONT HOSE REEL TO SHINE INTO MANHOLE		
H39B	TWO HIGH INTENSITY LED WORK LIGHTS (HELLA PB1500) ON FRONT HOSE REEL TO SHINE INTO MANHOLE		1
	STORAGE OPTIONS		
STD	25' FIRE HOSE BASKET		STANDARD
STD	TWO (2) GALVANIZED STEEL TUBE TRAYS		
I1	TWO (2) GALVANIZED STEEL TUBE TRAYS MOUNTED OVER TRI AXLES / TIRES - 13-1/2 FT LONG - USE WITH LIFT AXLE SELECTION		
I22	UPGRADE TUBE TRAYS TO STAINLESS STEEL		1
I22-B	UPGRADE ONE TUBE TRAY TO STAINLESS STEEL	(MOUNTED ON THE OPPOSITE SIDE OF OPTION I310 TOOLBOX)	
	TOOL BOX IN LIEU OF TUBE TRAY (CHOOSE ONE, PAIR, OR LESS)		
I310A-CS	STAINLESS STEEL CURBSIDE TOOL BOX IN LIEU OF TUBE TRAY, 120" LONG X 16" HIGH X 22" DEEP (WITH 2-FOLD UP DOORS) (P/N: BOX022458)		
I310A-DS	STAINLESS STEEL DRIVER'S SIDE TOOL BOX IN LIEU OF TUBE TRAY, 120" LONG X 16" HIGH X 22" DEEP (WITH 2-FOLD UP DOORS) (P/N: BOX022458)		
I310B-CS	STAINLESS STEEL CURBSIDE TOOL BOX IN LIEU OF TUBE TRAY, 148" LONG X 16" HIGH X 22" DEEP (WITH 2-FOLD UP DOORS) (P/N: BOX022429)	USE WITH LIFT AXLE	
I310B-DS	STAINLESS STEEL DRIVER'S SIDE TOOL BOX IN LIEU OF TUBE TRAY, 148" LONG X 16" HIGH X 22" DEEP (WITH 2-FOLD UP DOORS) (P/N: BOX022429)	USE WITH LIFT AXLE	
I310C-CS	STAINLESS STEEL CURBSIDE TOOL BOX IN LIEU OF TUBE TRAY, 92" LONG X 16" HIGH X 22" DEEP (WITH 2-FOLD UP DOORS)	USE WITH SINGLE REAR AXLE	
I310C-DS	STAINLESS STEEL DRIVER'S SIDE TOOL BOX IN LIEU OF TUBE TRAY, 92" LONG X 16" HIGH X 22" DEEP (WITH 2-FOLD UP DOORS)	USE WITH SINGLE REAR AXLE	
	30" TOOLBOX (CHOOSE ONE OR LESS)		
I8B-CS	30" TOOL BOX - ALUMINUM, 30" WIDE X 24" TALL X 24" DEEP, MOUNTED ON THE CURBSIDE		
I8B-DS	30" TOOL BOX - ALUMINUM, 30" WIDE X 24" TALL X 24" DEEP, MOUNTED ON THE DRIVER'S SIDE		
I8C-CS	30" TOOL BOX - STAINLESS STEEL, 30" WIDE X 24" HIGH X 24" DEEP, MOUNTED ON THE CURBSIDE		
I8C-DS	30" TOOL BOX - STAINLESS STEEL, 30" WIDE X 24" HIGH X 24" DEEP, MOUNTED ON THE DRIVER'S SIDE		1
	36" TOOLBOX (CHOOSE ONE OR LESS)		
I7B-CS	36" TOOL BOX - ALUMINUM, 36" WIDE X 24" TALL X 24" DEEP, MOUNTED ON THE CURBSIDE		
I7C-CS	36" TOOL BOX - STAINLESS STEEL, 36" WIDE X 24" HIGH X 24" DEEP, MOUNTED ON THE CURBSIDE		
	48" TOOLBOX (CHOOSE ONE OR LESS)		
I9B	48" TOOL BOX - ALUMINUM, 48" WIDE X 24" TALL X 24" DEEP, MOUNTED ON THE CURBSIDE		
I9C	48" TOOL BOX - STAINLESS STEEL, 48" WIDE X 24" HIGH X 24" DEEP, MOUNTED ON THE CURBSIDE		1
	60" TOOLBOX (CHOOSE ONE OR LESS)		
I27B	60" TOOL BOX - ALUMINUM, 60" WIDE X 24" TALL X 24" DEEP, MOUNTED ON THE CURBSIDE	CONSULT ENGINEERING	
I28C	60" TOOL BOX - STAINLESS STEEL, 60" WIDE X 24" HIGH X 24" DEEP, MOUNTED ON THE CURBSIDE	CONSULT ENGINEERING	
	72" TOOLBOX (CHOOSE ONE OR LESS)		

I4B	72" TOOL BOX - ALUMINUM, 72" WIDE X 24" HIGH X 24" DEEP, MOUNTED ON THE CURBSIDE	CONSULT ENGINEERING	
I4C	72" TOOL BOX - STAINLESS STEEL, 72" WIDE X 24" HIGH X 24" DEEP, MOUNTED ON THE CURBSIDE	CONSULT ENGINEERING	
	TUNNEL TOOLBOX (CHOOSE ONE OR LESS)		
I25B	TUNNEL TOOLBOX - ALUMINUM, 30" HIGH X 24" WIDE X 50" DEEP		
I25C	TUNNEL TOOLBOX - STAINLESS STEEL, 30" HIGH X 24" WIDE X 50" DEEP		
	VERTICAL TOOLBOX ON BURNER MOUNT (CHOOSE ONE OR LESS)		
I303C-CS	VERTICAL ALUMINUM TOOLBOX ON BURNER MOUNT 24" X 24" X 48", NO SHELF		
I303D-CS	VERTICAL ALUMINUM TOOLBOX ON BURNER MOUNT 24" X 24" X 48" WITH SHELF		
I303E-CS	VERTICAL STAINLESS STEEL TOOLBOX ON BURNER MOUNT 24" X 24" X 48", NO SHELF (P/N: BOX022524)		
I303F-CS	VERTICAL STAINLESS STEEL TOOLBOX ON BURNER MOUNT 24" X 24" X 48" WITH SHELF (P/N: BOX022523)		
	TUBE RACKS		
I13B-CS	TUBE RACK - THREE TUBES - FOLD DOWN WITH SPRING ASSIST, CURBSIDE	(TUBES NOT INCLUDED)	1
I13B-DS	TUBE RACK - THREE TUBES - FOLD DOWN WITH SPRING ASSIST, DRIVER'S SIDE	(TUBES NOT INCLUDED)	
	OTHER OPTIONS		
I10	HAND GUN HOLDER - TOP OF CURBSIDE TOOL BOX		1
I14	TRAFFIC CONE HOLDER ON DRIVER'S SIDE		1
I14C	TRAFFIC CONE HOLDER ON CURBSIDE		1
I15	WATER COOLER HOLDER WITH 5 GALLON COOLER		
I16A	WHEEL CHOCK HOLDER (PER SIDE) - DRIVER'S SIDE		1
I16B	WHEEL CHOCK HOLDER (PER SIDE) - CURBSIDE		1
I17A	NOZZLE RACK - SIX (6) NOZZLES, 1"		
I17B	NOZZLE RACK - SIX (6) NOZZLES, 3/4"		1
I20A	REAR DRAIN HOSE RACK FOR 6" LAYFLAT HOSE X 15' LONG		1
	TWO BUMPER TOOLBOXES (CHOOSE ONE OR LESS)		
I26B	TWO BUMPER TOOL BOXES - ALUMINUM, 16" HIGH X 12" WIDE X 18" DEEP WITH FOLD DOWN DOOR		
I26C	TWO BUMPER TOOL BOXES - STAINLESS STEEL, 16" HIGH X 12" WIDE X 18" DEEP WITH FOLD DOWN DOOR		1
	CHASSIS OPTIONS		
STD	DOT LIGHTING / FENDERS / MUD FLAPS / TAILGATE SAFETY PROP, ICC LIGHTS		STANDARD
STD	REMOTE ACTUATED BODY SAFETY PROP		STANDARD
STD	70 GALLONS AW-46 HYDRAULIC OIL, LEVEL/TEMPERATURE GAUGE, SHUTOFF ON SUCTION		STANDARD
STD	REAR BUMPER, TRIANGLE KIT, FIRE EXTINGUISHER, BACKUP ALARM		STANDARD
STD	ALLISON 10-BOLT PTO UPGRADE		STANDARD
J000	MID-SHIP MOUNTED (SPLIT-SHAFT) TRANSFER CASE WITH TOP DISCONNECT		1
J001	MUST BE "OMSI" BRAND TRANSFER CASE		1
J002	MUST BE "NAMCO" BRAND TRANSFER CASE		

J-CNG	CNG POWERED CHASSIS UPFIT		
J0	FRONT BUMPER		
J0B	FRONT BUMPER - CALIFORNA FRONT BUMPER		1
J2	TRANSFER CASE OIL LEVEL SIGHT GLASS / FILL, MOUNTED ON DRIVER'S SIDE FRAME RAIL (PN: GAU006456)		1
J3	TOW HOOKS FRONT		1
J4B	TOW HOOKS REAR - FRAME MOUNTED		1
J4A	TOW HOOKS REAR - HEAVY DUTY WELDED	REQUIRES J16	
J11	RELOCATE REAR AXLES - 18" OR LESS		
J12-SS	STAINLESS STEEL METAL MUD FLAPS IN FRONT OF REAR TIRES	SS MUD FLAP UPGRADE	1
J14	DROP AXLE, 13,200 LB , SELF STEER - MOUNTED IN PUSHER POSITION	CONSULT ENGINEERING	
J14B	DROP AXLE , 9,000 LB , SELF STEER - MOUNTED IN TAG POSITION	CONSULT ENGINEERING	
J14C	DROP AXLE, 20,000 LB, SELF STEER - MOUNTED IN PUSHER POSITION	CONSULT ENGINEERING	
J16D	3/4" WELDED PINTLE PLATE WITH DUAL GUSSETS AND REMOVABLE REAR STEP BUMPER		
J18	REMOTE LUBE OF TAILGATE LIFT COMPONENTS AND TAILGATE LOCKS		1
J22	STAINLESS STEEL DUMP APRON / PAN ON REAR BUMPER	NOT COMPATIBLE WITH J16	
J303	ADD HYDRAULIC OIL COOLER TO CIRCUIT	REQUIRED WITH OPTION D301* OR OPTION D27*	
J303A	ADD DUAL HYDRAULIC OIL COOLERS TO CIRCUIT	REQUIRED WITH OPTION D307HM	
J303	ADD HYDRAULIC OIL COOLER TO CIRCUIT		
J303A	ADD DUAL HYDRAULIC OIL COOLERS TO CIRCUIT		
PAINT OPTIONS			
STD	PAINTED WITH PPG URETHANE PAINT		STANDARD
STD	PAINT BODY WHITE		STANDARD
STD	PAINT FRAME AND PARTS BLACK		STANDARD
STD	PAINT HOSE REEL AND BOOM BLACK		STANDARD
FINISH PACKAGE (CHOOSE ONE OR LESS)			
STD	FLEET FINISH		STANDARD
K100	ELITE FINISH - INCLUDES SANDING BETWEEN COATS		
K200	SIGNATURE FINISH - INCLUDES SANDING AND DEFLEET METALLIC PAINT	INCLUDES K10, K13, K14	
STRIPES AND TAPES (CHOOSE ANY)			
K3	PAINT CAB & DOOR JAMB - SINGLE COLOR - PAINT CODE # REQUIRED:	PAINT CODE # REQUIRED	
K5	REAR DOOR CHEVRON STRIPING - VINYL		
K6	CONSPICUITY REFLECTIVE TAPE		1
COMPONENT UPGRADES (CHOOSE ANY)			
K9	PAINT FRAME ANY COLOR OTHER THAN BLACK	PAINT CODE # REQUIRED	
K10	PAINT BODY ANY COLOR OTHER THAN WHITE	PAINT CODE # REQUIRED	

K13	PAINT PARTS ANY COLOR OTHER THAN BLACK	PAINT CODE # REQUIRED	
K14	PAINT BOOM, CONTROL BOX AND HOSE REEL ANY COLOR OTHER THAN BLACK	PAINT CODE # REQUIRED	
OTHER OPTIONS (CHOOSE ANY)			
K20	INTERIOR DEBRIS TANK COATING	NOT WARRANTIED	
K21	CUSTOM DECAL PACKAGE		
MISCELLANEOUS OPTIONS			
STD	25 FEET OF VACUUM TUBING (5) AND CLAMPS		STANDARD
STD	TIGER TAIL HOSE GUIDE		STANDARD
STD	TWO SEWER CLEANING NOZZLES		STANDARD
VACUUM TUBING			
M0	UPGRADE VACUUM TUBING TO FLAT FLANGE	8" FLAT FLANGE	1
HOSES (CHOOSE ANY)			
M3	FILL HOSE 25' X 2 1/2"		1
M4	FILL HOSE 50' X 2 1/2"		
M5	LEADER HOSE 10' X 1"		
M5A	LEADER HOSE 20' X 1"		
M5B	LEADER HOSE 10' X 3/4"		1
M5C	LEADER HOSE 25' X 1"		
JETTER HOSE (CHOOSE ONE OR LESS)			
M6A	TEST FOR DEALER SUPPLIED SEWER HOSE		
M7C	1-1/4" PIRANHA SEWER HOSE - 2,500 PSI X 500 FT PLASTIC (ORANGE) (PN:HOS022433)		
M7E	1" COBRA SEWER HOSE - 2,500 PSI X 500 FT PLASTIC (ORANGE) (PN: HOS022484)		
M7G	3/4" COBRA SEWER HOSE - 2,500 PSI X 500 FT PLASTIC (ORANGE) (PN: HOS022486)		
M7H	3/4" COBRA SEWER HOSE - 3,000 PSI X 500 FT PLASTIC (BLUE) (PN: HOS022487)		
M7I	3/4" PIRHANA SEWER HOSE - 3,000 PSI X 500 FT PLASTIC (BLUE) (PN: HOS022497)		
M7J	1" PIRHANA SEWER HOSE - 2,500 PSI X 500 FT PLASTIC (ORANGE) (PN: HOS022500)		
M8	1" PREDATOR SEWER HOSE - 2,500 PSI X 600 FT PLASTIC (ORANGE) (HOS022342)		
M8C	1" COBRA SEWER HOSE - 2,500 PSI X 600 FT PLASTIC (ORANGE) (PN: HOS022488)		
M8D	1" COBRA SEWER HOSE - 3,000 PSI X 600 FT PLASTIC (BLUE) (PN: HOS022489)		
M8G	1" PIRHANA SEWER HOSE - 2,500 PSI X 600 FT PLASTIC (ORANGE) (PN: HOS022393)		
M8H	1" PIRHANA SEWER HOSE - 3,000 PSI X 600 FT PLASTIC (BLUE) (PN: HOS022496)		
M8I	3/4" PIRANHA SEWER HOSE - 3,000 PSI X 600 FT PLASTIC (BLUE) (PN: HOS022498)		
M9C	1" COBRA SEWER HOSE - 2,500 PSI X 800 FT PLASTIC (ORANGE) (PN: HOS022492)		
M9D	1" COBRA SEWER HOSE - 3,000 PSI X 800 FT PLASTIC (BLUE) (PN: HOS022493)		
M9F	3/4" COBRA SEWER HOSE - 3,000 PSI X 800 FT PLASTIC (BLUE) (PN: HOS022495)		1

M9G	1" PIRANHA SEWER HOSE - 2,500 PSI X 800 FT PLASTIC (ORANGE) (PN: HOS022332)	
M9H	1" PIRANHA SEWER HOSE - 3,000 PSI X 800 FT PLASTIC (BLUE) (PN: CAT022382)	
M9I	3/4" PIRANHA SEWER HOSE - 3,000 PSI X 800 FT PLASTIC (BLUE) (PN: HOS022499)	
ACCESSORIES (CHOOSE ANY)		
M10	HYD. TOOL SPOOL & NEEDLE VALVE – CURB SIDE (ADJ. 3-13 GPM)	
M11	HYDRAULIC TOOL CIRCUIT HOSE REEL WITH 50' X ½" HOSE TWIN HOSE	INCLUDES OPTION M10
M12	MANHOLE LIFTING HOOK	1
M13	HYDRANT WRENCH	1
M15	ADDITIONAL OPERATIONS AND MAINTENANCE MANUAL - EACH	1
M26	1" SIX WIRE EXTENDER	
M26A	3/4" SIX WIRE EXTENDER PN: NOZ022506	
M27	TIGER TAIL (TOTAL OF TWO)	1
M28	(5) TRAFFIC CONES - 28" LIME GREEN WITH REFLECTIVE STRIPE	
BACKUP CAMERA (CHOOSE ONE OR LESS)		
M29	ONE CAMERA - BACK-UP CAMERA SYSTEM WITH 7" COLOR MONITOR (RV-505A), INCLUDES DVR-916 REAR CAMERA	
M29B	TWO CAMERA - BACK-UP CAMERA SYSTEM WITH 7" COLOR MONITOR (RV-505A), INCLUDES DVR-916 REAR AND DVR-921 FRONT CAMERA	
M29C	THREE CAMERA - BACK-UP CAMERA SYSTEM WITH 7" COLOR MONITOR (RV-505A), INCLUDES DVR-916 REAR AND TWO (2) DVR-920 SIDE CAMERAS. SIDE CAMERAS TO ACTIVATE WITH TURN SIGNALS	
M29D	FOUR CAMERA - BACK-UP CAMERA SYSTEM WITH 7" COLOR MONITOR (RV-805A), INCLUDES DVR-916 REAR, DVR-921 FRONT, AND TWO (2) DVR-920 SIDE CAMERAS. SIDE CAMERAS TO ACTIVATE WITH TURN SIGNALS	1
OTHER OPTIONS		
M30A	GROENEVELD EP-0 SINGLELINE AUTOMATED LUBRICATION SYSTEM - BODY ONLY, P/N: ACC022823	E6 IS REQUIRED
M30C	GROENEVELD EP-0 SINGLELINE AUTOMATED LUBRICATION SYSTEM - BODY AND CHASSIS, P/N: ACC022835	E6 IS REQUIRED
M33	ADAPTER: 8" MALE TO 6" MALE CAMLOCK	
M33-RL	ADAPTER: 8" TO 6" RINGLOCK REDUCER (P/N: PIP008688)	
M34	RING-LOCK ALUMINUM VACUUM TUBE, 8" X 58-IN LONG X 0.072" WALL, WELD-ON CAST ALUMINUM RING-LOCK ENDS (P/N: PIP008549)	STANDARD 8" VAC TUBE
M34A	FLAT FLANGE ALUMINUM VACUUM TUBE, 8" X 5-FT LONG X 0.090" WALL, WELD-ON CAST ALUMINUM FLAT FLANGE ENDS (P/N: PIP008555)	8" FLAT FLANGE
M35	ADDITIONAL 8" TUBE CLAMP, EACH (P/N: CLA000978)	STANDARD 8" VAC CLAMP
M35A	ADDITIONAL 8" FLAT FLANGE TUBE CLAMP (P/N: CLA001041)	8" FLAT FLANGE
M36	HEAVY DUTY ALUMINUM HX TUBE, 8" X 6-FT LONG X 0.090" WALL WITH PRESSED IN STEEL ENDS AND SOFT TIP CUFF END (P/N: PIP008558 & GAS023037)	SOFT TIP
M36A	FLAT FLANGE HEAVY DUTY ALUMINUM HX TUBE, 8" X 6-FT LONG X 0.090" WALL TUBE, WELD-ON CAST FLAT FLANGE X PRESSED IN STEEL MALE RING-LOCK END, SOFT TIP CUFF END (P/N: PIP008711 & GAS023037)	8" FLAT FLANGE SOFT TIP
M37	HEAVY DUTY ALUMINUM HX TUBE, 8" X 5-FT LONG X 0.090" WALL WITH PRESSED IN STEEL ENDS AND SOFT TIP CUFF END (P/N: PIP008550 & GAS023037)	SOFT TIP
M37A-LIGH	FLAT FLANGE ALUMINUM HX TUBE, 8" X 5-FT LONG X 0.072" WALL TUBE, WELD-ON CAST FLAT FLANGE X WELD-ON CAST ALUMINUM MALE RING-LOCK END, SOFT TIP CUFF END (P/N: PIP022316 & P/N: GAS023037)	8" FLAT FLANGE SOFT TIP
M38A	ALUMINUM TUBE, 8" X 3-FT LONG X 0.072" WALL, WELDED ALUMINUM ENDS WITH BOLT ON STEEL CROWN (P/N: PIP008527 & F012477)	CROWN TIP
M38C	ALUMINUM TUBE, 8" X 5-FT LONG X 0.072" WALL, WELDED ALUMINUM ENDS WITH BOLT ON STEEL CROWN (P/N: PIP008549 & F012477)	CROWN TIP

M38C-FF	FLAT FLANGE ALUMINUM HX TUBE, 8" X 5-FT LONG X 0.072" WALL TUBE, WELD-ON CAST FLAT FLANGE X PRESSED IN STEEL MALE RING-LOCK END, BOLT ON STEEL CROWN (P/N: PIP022316 & F012477) (P/N: NOZ007965)	8" FLAT FLANGE CROWN TIP	
M38D	ALUMINUM TUBE, 8" X 6-FT LONG X 0.072" WALL, WELDED ALUMINUM ENDS WITH BOLT ON STEEL CROWN (P/N: PIP020729 & F012477)	CROWN TIP	
M38D-FF	FLAT FLANGE HEAVY DUTY ALUMINUM HX TUBE, 8" X 6-FT LONG X 0.090" WALL TUBE, WELD-ON CAST FLAT FLANGE X PRESSED IN STEEL MALE RING-LOCK END, BOLT ON STEEL CROWN (P/N: PIP008711 & F012477) (P/N: CAT025623)	8" FLAT FLANGE CROWN TIP	
M39A	HEAVY DUTY ALUMINUM HX TUBE, 8" X 6-FT LONG X 0.090" WALL WITH PRESSED IN STEEL ENDS AND WATER RING (P/N: A051724, F012477, PIP008558, & NOZ020610)	WATER RING	
CUSTOM OPTIONS			

**			
	PRE-DELIVERY INSPECTION TRIP 2 EMPLOYEES, 3 DAYS, 2 NIGHTS		
	CUSTOM CENTER CONSOLE STORAGE		
	OPTIONS H1B AND H2B - USE WHELEN L31'S IN LIEU OF L10'S		
	OPTION I26C - ENSURE NOZZLE RACK IS ON DRIVER'S SIDE (CURBSIDE STORAGE TO BE USED FOR CLAMPS)		
	OPTION I14 - IN LIEU OF CONE HOLDER ON DRIVER'S SIDE, MOUNT SECOND CONE HOLDER AT CURBSIDE REAR (TOTAL OF TWO CONE HOLDERS CURBSIDE)		



PRICING SUMMARY

PRICE OF BASE UNIT WITH OPTIONS:		\$ 746,580.87
SOURCWELL DISCOUNT:		\$ 64,204.71
DELIVERY: (\$1,000.00 MINIMUM)	@ \$4.00 PER MILE	\$ 11,325.00
ESTIMATED SUBTOTAL:		\$ 693,701.16
SALES TAX:		\$ 73,355.44
TOTAL PRICE (PER UNIT):		\$ 767,056.60

ALL PRICES ARE IN US DOLLARS

ALL ORDERS ARE SUBJECT TO CURRENT PRICES IN EFFECT AT THE TIME OF ORDER ACKNOWLEDGMENT. PRICES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. PRICING DISCLAIMER: WHILE WE MAKE EVERY EFFORT TO MAINTAIN AND PRESERVE PRICING ACCURACY, ALL COST INCREASES INCURRED AFTER ORDER ACKNOWLEDGMENT FOR MAJOR COMPONENTS AND GOVERNMENT MANDATED REQUIREMENTS, TARIFFS, AND RAW MATERIAL SURCHARGES WILL BE PASSED THROUGH AND ADDED TO CUSTOMER INVOICES WITH OR WITHOUT NOTICE. ALTHOUGH THE INFORMATION ON THIS QUOTATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE CORRECT AT THE TIME OF PRINTING, WE MAKE NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THIS INFORMATION. WE RESERVE THE RIGHT TO CHANGE, DELETE, OR OTHERWISE MODIFY THE PRICING INFORMATION WHICH IS REPRESENTED HEREIN WITHOUT ANY PRIOR NOTICE. WE CAREFULLY CHECK PRICING SPECIFICATIONS, BUT OCCASIONALLY ERRORS CAN OCCUR, THEREFORE WE RESERVE THE RIGHT TO CHANGE SUCH PRICES WITHOUT NOTICE. WE DISCLAIM ALL LIABILITY FOR ANY ERRORS OR OMISSIONS IN THE MATERIALS. IN NO EVENT WILL WE BE RESPONSIBLE FOR ANY DAMAGES OF ANY NATURE WHATSOEVER FROM THE RELIANCE UPON INFORMATION FROM THESE MATERIALS. PLEASE CHECK YOUR ORDER TO CONFIRM YOUR PRICING INFORMATION