

Appendix C

Energy Technical Report

ALCO IRON AND METAL

Energy Technical Report

Prepared by:



September 17, 2024

TABLE OF CONTENTS

INTRODUCTION	3
SETTING.....	4
Regulatory Setting.....	4
Federal	4
Energy Policy and Conservation Act	4
Energy Policy Act of 1992 and 2005.....	4
Energy Independence and Security Act of 2007	4
State	5
Integrated Energy Policy Report	5
Senate Bill 1078, 350 and 100: California Renewables Portfolio Standard Program	5
Senate Bill X1-2: California Renewable Energy Resources Act	5
Energy Action Plan	6
Assembly Bill 1007: State Alternatives Fuel Plan.....	6
California Building Energy Efficiency Standards (Title 24, Part 6).....	6
California Green Building Standards Code (Title 24, Part 11).....	7
Local	7
San Leandro 2035 GEneral Plan	7
San Leandro 2021 Climate Action Plan	7
Environmental Setting	7
Electricity.....	7
Petroleum-Based Fuels	7
STANDARDS OF SIGNIFICANCE	8
IMPACTS AND MITIGATION MEASURES	9
Impact Analysis	9
IMPACT ENERGY-1	9
Construction Energy Usage.....	9
Operational Energy Usage	10
Conclusion.....	10
Mitigation Measures ENERGY-1.....	11
IMPACT ENERGY-2	11
Mitigation Measures ENERGY-2.....	11
IMPACT ENERGY-3	11
Mitigation Measures ENERGY-3.....	11
CONCLUSION	12
ATTACHMENTS	
ATTACHMENT A – CALEEMOD MODELING OUTPUT AND FUEL CONVERSION CALCULATIONS	
ATTACHMENT B – DIESEL FUEL USE REDUCTION FROM REDUCED IDLING	

INTRODUCTION

This Energy Technical Report (Report) addresses potential energy use and conservation impacts associated with the proposed additional use of a two-acre parcel for storage and processing of metal scrap for Alco Iron & Metal operations (the “project”) at Doolittle Drive and Eden Road in San Leandro, CA. The primary purpose of the project is to relocate the large scrap metal piles away from view from Doolittle Drive and allow for better traffic circulation onsite. The additional two acres will be used to store materials for processing and allow for better circulation of truck traffic and required storm water treatment measures. A new truck scale will also be added on the existing site to allow for separate in-bound and out-bound truck scales, which will facilitate more efficient truck circulation and help eliminate queuing. The project also includes the replacement of a frontage wall and landscaping installation.

As directed by the City of San Leandro, this Energy Technical Report includes the following:

- Existing conditions, including applicable regulatory framework pertaining to energy conservation and energy suppliers for the project area.
- Quantified project construction energy estimate: Energy use associated with short-term construction activities were quantified using the California Emissions Estimator Model (CalEEMod) Version 2022.1¹
- Quantified energy use estimate associated with long-term operational activities: Fuel use associated with equipment and vehicle operations, as well as fuel/energy use associated with the operation of stationary sources.

The project would consume petroleum-based fuels during construction for onsite heavy equipment and vehicles (worker automobiles and haul trucks). The project would also consume a small amount of electricity from the additional truck scale and would decrease fuel consumption by reducing truck idling through improved truck circulation during project operations. This Energy Technical Report provides an analysis of potential energy use and conservation impacts that would result from the implementation of the project.

¹ California Air Pollution Control Officers Association (CAPCOA). 2022. California Emissions Estimator Model User’s Guide Version 2022.1. April 2022.

SETTING

REGULATORY SETTING

FEDERAL

ENERGY POLICY AND CONSERVATION ACT

The Energy Policy and Conservation Act of 1975 established nationwide fuel economy standards to conserve oil. Pursuant to this Act, the National Highway Traffic and Safety Administration, part of the U.S. Department of Transportation (DOT), is responsible for revising existing fuel economy standards and establishing new vehicle economy standards.

The Corporate Average Fuel Economy (CAFE) program was established to determine vehicle manufacturer compliance with the government's fuel economy standards. Compliance with the CAFE standards is determined based on each manufacturer's average fuel economy for the portion of their vehicles produced for sale in the country. EPA calculates a CAFE value for each manufacturer based on the city and highway fuel economy test results and vehicle sales. The CAFE values are a weighted harmonic average of the EPA city and highway fuel economy test results. Based on information generated under the CAFE program, DOT is authorized to assess penalties for the Energy Independence and Security Act of 2007 (described below).

ENERGY POLICY ACT OF 1992 AND 2005

The Energy Policy Act of 1992 (EPAct) was passed to reduce the country's dependence on foreign petroleum and improve air quality. The EPAct includes several parts intended to build an inventory of alternative fuel vehicles in large, centrally-fueled fleets in metropolitan areas. The EPAct requires certain federal, state, and local government and private fleets to purchase a percentage of light-duty alternative fuel vehicles. In addition, financial incentives are also included in The EPAct. Federal tax deductions are allowed for businesses and individuals to cover the incremental cost of alternative fuel vehicles. States are also required by The EPAct to consider a variety of incentive programs to help promote alternative fuel vehicles. The Energy Policy Act of 2005 provides renewed and expanded tax credits for electricity generated by qualified energy sources, such as landfill gas; provides bond financing, tax incentives, grants, and loan guarantees for clean renewable energy and rural community electrification; and establishes a federal purchase requirement for renewable energy.

ENERGY INDEPENDENCE AND SECURITY ACT OF 2007

The Energy Independence and Security Act of 2007 is designed to improve vehicle fuel economy and help reduce U.S. dependence on oil. It represents a major step forward in expanding the production of renewable fuels, reducing dependence on oil, and confronting global climate change. The Energy Independence and Security Act of 2007 increases the supply of alternative fuel sources by setting a mandatory Renewable Fuel Standard requiring fuel producers to use at least 36 billion gallons of biofuel in 2022.

By addressing renewable fuels and the CAFE standards, the Energy Independence and Security Act of 2007 builds on progress made by the Energy Policy Act of 2005 in setting out a comprehensive national energy strategy for the 21st century.

STATE

INTEGRATED ENERGY POLICY REPORT

Senate Bill (SB) 1389 (Chapter 568, Statutes of 2002) required the CEC to: “conduct assessments and forecasts of all aspects of energy industry supply, production, transportation, delivery and distribution, demand, and prices. The Energy Commission shall use these assessments and forecasts to develop energy policies that conserve resources, protect the environment, ensure energy reliability, enhance the state’s economy, and protect public health and safety” (Public Resources Code Section 25301(a)). This work culminated in the Integrated Energy Policy Report (IEPR).

CEC adopts an IEPR every two years and an update every other year. The 2022 IEPR is the most recent IEPR, which was adopted in February 2023. The 2022 IEPR provides a summary of priority energy issues currently facing the State, outlining strategies and recommendations to further the State’s goal of ensuring reliable, affordable, and environmentally-responsible energy sources.²

SENATE BILL 1078, 350 AND 100: CALIFORNIA RENEWABLES PORTFOLIO STANDARD PROGRAM

SB 1078 (Chapter 516, Statutes of 2002) establishes a renewable portfolio standard (RPS) for electricity supply. The RPS required that retail sellers of electricity, including investor-owned utilities and community choice aggregators, provide 20 percent of their supply from renewable sources by 2017. The program was accelerated in 2015 with SB 350, which mandated a 50 percent RPS by 2030. SB 350 includes interim annual RPS targets with three-year compliance periods and requires 65% of RPS procurement to be derived from long-term contracts of 10 or more years. In 2018, SB 100 was signed into law, which again increases the RPS to 60% by 2030 and requires all the state’s electricity to come from carbon-free resources by 2045.

SENATE BILL X1-2: CALIFORNIA RENEWABLE ENERGY RESOURCES ACT

SB X1-2 of 2011 requires all California utilities to generate 33 percent of their electricity from renewables by 2020. SB X1-2 sets a three-stage compliance period requiring all California utilities, including independently-owned utilities, energy service providers, and community choice aggregators, to generate 20 percent of their electricity from renewables by December 31, 2013; 25 percent by December 31, 2016; and 33 percent by December 31, 2020. SB X1-2 also requires the renewable electricity standard to be met increasingly with renewable energy that is supplied to the California grid from sources within, or directly proximate to, California. SB X1-2 mandates that renewables from these sources make up at least 50 percent of the total renewable energy for the 2011-2013 compliance period, at least 65 percent for the 2014-2016 compliance period, and at least 75 percent for 2016 and beyond.

² California Energy Commission (CEC). 2023. Final 2022 Integrated Energy Policy Report. February 2023.

ENERGY ACTION PLAN

The first Energy Action Plan (EAP) emerged in 2003 from a crisis atmosphere in California's energy markets. The State's three major energy policy agencies (CEC, CPUC, and the Consumer Power and Conservation Financing Authority [established under deregulation and now defunct]) came together to develop one high-level, coherent approach to meeting California's electricity and natural gas needs. It was the first time that energy policy agencies formally collaborated to define a common vision and set of strategies to address California's future energy needs and emphasize the importance of the impacts of energy policy on the California environment.

In the October 2005 Energy Action Plan II, CEC and CPUC updated their energy policy vision by adding some important dimensions to the policy areas included in the original EAP, such as the emerging importance of climate change, transportation-related energy issues and research and development activities. CEC recently adopted an update to the EAP II in February 2008 that supplements the earlier EAPs and examines the State's ongoing actions in the context of global climate change.

ASSEMBLY BILL 1007: STATE ALTERNATIVES FUEL PLAN

Assembly Bill (AB) 1007 (Chapter 371, Statutes of 2005) required the CEC to prepare a state plan to increase the use of alternative fuels in California. The CEC prepared the State Alternative Fuels Plan (SAF Plan) in partnership with the California Air Resources Board (CARB) and in consultation with other State, federal, and local agencies. The SAF Plan presents strategies and actions California must take to increase the use of alternative non-petroleum fuels in a manner that minimizes the costs to California and maximizes the economic benefits of in-state production. The SAF Plan assessed various alternative fuels and developed fuel portfolios to meet California's goals to reduce petroleum consumption, increase alternative fuel use, reduce greenhouse gas (GHG) emissions, and increase in-state production of biofuels without causing a significant degradation of public health and environmental quality.

CALIFORNIA BUILDING ENERGY EFFICIENCY STANDARDS (TITLE 24, PART 6)

The energy consumption of new residential and nonresidential buildings in California is regulated by the state's Title 24, Part 6, Building Energy Efficiency Standards (California Energy Code). The California Energy Code was established by CEC in 1978 in response to a legislative mandate to create uniform building codes to reduce California's energy consumption and provide energy efficiency standards for residential and nonresidential buildings. CEC updates the California Energy Code every 3 years with more stringent design requirements for reduced energy consumption, which results in the generation of fewer GHG emissions.

The 2025 California Energy Code will be adopted in 2024 and will apply to projects constructed after January 1, 2026. The building efficiency standards are enforced through the local plan check and building permit process. Local government agencies may adopt and enforce additional energy standards for new buildings as reasonably necessary in response to local climatologic, geologic, or topographic conditions, provided that these standards exceed those in the California Energy Code.

CALIFORNIA GREEN BUILDING STANDARDS CODE (TITLE 24, PART 11)

The California Green Building Standards Code (CALGreen) is part 11 of Title 24, California Code of Regulations. CALGreen is the first-in-the-nation mandatory green building standards code, developed in an effort to meet the goals of California's landmark initiative AB 32, which established a comprehensive program of cost-effective reductions of GHG emissions to 1990 levels by 2020. CALGreen includes a waste diversion mandate, which requires that at least 65 percent of construction materials generated during new construction or demolition projects are diverted from landfills.

LOCAL

SAN LEANDRO 2035 GENERAL PLAN

The City of San Leandro adopted its 2035 General Plan in September 2016. The 2035 General Plan covers 2015 through 2035. State law requires every city and 20-year in California to prepare a long-range "General Plan" which guides decisions about future growth. There are no policies related to energy efficiency or renewable energy from the 2035 General Plan applicable to the project.

SAN LEANDRO 2021 CLIMATE ACTION PLAN

The City of San Leandro adopted its 2021 Climate Action Plan (CAP) in July 2021. The 2021 CAP is the City's comprehensive strategy to reduce greenhouse gas (GHG) emissions and to adapt to changing climate conditions. The CAP allows City decision-makers, staff, and the community to understand the sources and magnitude of local GHG emissions and the impacts of climate change on the community, reduce GHG emissions, prioritize steps to achieve GHG emission-reduction targets, and increase resilience. There are no reduction strategies in the 2021 CAP applicable to the project.

ENVIRONMENTAL SETTING

ELECTRICITY

Electrical service to the facility is provided by PG&E. In 2023, statewide electricity generation was 215,625 gigawatt hours (GWh) of electric power.³ The project would require a small amount of electricity consumption from the additional scale (approximately 1,000 kilowatt hours [kWh] of electricity annually).

PETROLEUM-BASED FUELS

The project would consume petroleum-based fuels during construction for onsite equipment and vehicles (worker automobiles and haul trucks). The project would decrease operational fuel consumption through reducing truck idling by improving truck circulation. In 2022, annual gasoline sales were approximately 13.6 billion gallons, and annual diesel fuel sales were approximately 3.6 billion gallons⁴

³ California Energy Commission. 2024. Electric Generation Capacity and Energy. <https://www.energy.ca.gov/data-reports/energy-almanac/california-electricity-data/electric-generation-capacity-and-energy>. Accessed on September 17, 2024.

⁴ California Energy Commission (CEC). 2024. Transportation Energy. <https://www.energy.ca.gov/data-reports/energy-almanac/transportation-energy>. Accessed on September 17, 2024.

STANDARDS OF SIGNIFICANCE

The standards of significance for the analysis of potential energy impacts are based on the new Energy section in Appendix G of the CEQA Guidelines.

Would the project:

- Result in potentially significant environmental impact due to wasteful, inefficient, or unnecessary consumption of energy resources during project construction or operation?
- Conflict with or obstruct a state or local plan for renewable energy or energy efficiency?

Neither the CEQA Guidelines nor Public Resources Code Section 21100(b)(3) provide a specific threshold for impacts associated with energy consumption. However, Appendix F of the CEQA Guidelines (14 CCR 15000 et seq.) provides guidance for evaluating whether a development project may result in significant impacts with regard to energy. Based on Appendix F of the CEQA Guidelines and the new Appendix G questions, the standards of significance for this analysis will evaluate whether the project would:

1. Result in wasteful, inefficient, or unnecessary consumption of energy.
2. Conflict with or obstruct a state or local plan for renewable energy or energy efficiency.
3. Require the construction of new or expanded energy production facilities or infrastructure, the construction of which could cause significant environmental impacts.

In evaluating the standards, the analysis will consider the scale of the project's energy use (size of the project) and project's energy conserving features.

IMPACTS AND MITIGATION MEASURES

The project would consume energy in two primary forms:

- Petroleum-based fuels (gasoline and diesel) and possibly electricity to power construction equipment, haul trucks, and worker vehicles during project construction; and
- Electricity to power the additional truck scale during project operations.

The project would also decrease petroleum-based fuel consumption during project operations by reducing truck idling through improved truck circulation.

The project is not responsible for developing these energy supplies. The project is not involved in the extraction and refining of petroleum and does not build or operate power plants. It is reasonably assumed that the companies and public utilities involved in these activities have previously undergone the appropriate environmental review pursuant to CEQA. Therefore, the analysis presented in this report is focused solely on the consumption of existing energy supplies by the project, and whether that consumption could be considered wasteful, inefficient, or unnecessary.

IMPACT ANALYSIS

IMPACT ENERGY-1

Project construction and operations would not result in a potentially significant environmental impact due to wasteful, inefficient, or unnecessary consumption of energy resources. (Less than Significant)

CONSTRUCTION ENERGY USAGE

Project construction would require site grading, paving, old wall demolition, new wall construction, broken pavement repair, and installation of the new truck scale. Construction would be very limited and the project site does not include unusual challenges that would require unusually high energy usage. Construction would be short term (approximately 31 working days) and would require various pieces of equipment such as a backhoe, grader, forklift, paving equipment, and concrete trucks. The project would not require the import/export of soil material from grading. Approximately 16 round haul truck trips would be required for bringing construction materials (paving materials and new scale) to the project site and approximately 8 haul truck round trips would be required for hauling the demolished frontage wall, as indicated in the CalEEMod modelling estimates in **Attachment A**.

Fuel consumption during construction was estimated using standard fuel consumption conversion factors and emissions modeling results from CalEEMod, a Statewide land use emissions computer model developed for the California Air Pollution Officers Association (CAPCOA) in collaboration with the California Air Districts. The model inputs assumed project construction would occur eight hours per day over approximately 31 working days. CalEEMod calculated the emissions and related fuel use for each construction phase including site grading, paving including broken pavement repair, old wall demolition, new wall construction, and installation of the new truck scale.

Based on CalEEMod results for project construction and standard fuel consumption conversion factors⁵, construction would require approximately 129 gallons of gasoline and 3,863 gallons of diesel fuel (See **Attachment A** for fuel consumption calculations). This includes all off-road construction equipment, hauling, and worker trips over the construction period. For the scale installation/construction, some electricity may be used (e.g., for power tools). While this electricity usage cannot be quantified at this time, it would be negligible compared to normal business operations, especially considering only one day would be required to install the new scale. When not in use, electric equipment would be powered off to avoid unnecessary energy consumption. Natural gas would not be used during construction.

OPERATIONAL ENERGY USAGE

Once the project is operational, approximately 1,000 kilowatt hours (kWh) of electricity would be required annually to power the additional truck scale during project operations. This electricity is considered very minor, since in 2020 the average annual electricity consumption for a U.S. residential utility customer was approximately 11,000 kWh per year.⁶

The project would also decrease petroleum-based fuel consumption (assumed to be primarily diesel) during project operations by reducing truck idling through improved truck circulation. It is estimated that on average approximately 90 vehicles queue at the scale per day and that each vehicle idles for approximately 10 minutes while onsite. The project would not increase throughput or vehicles at the site but would result in an estimated 50 percent reduction in truck idling through improved truck circulation and reduced queueing time. According to the U.S. Department of Energy, a heavy-duty truck consumes approximately 0.8 gallons of fuel per hour of idling.⁷ Thus, the project would result in a reduction of 6 gallons of diesel fuel per day or 2,190 gallons of diesel fuel per year (this calculation is presented in **Attachment B**).

CONCLUSION

As noted previously, electricity usage during short-term construction activities and long-term operations would be insignificant. While the project would consume petroleum-based fuels (primarily diesel) during short-term construction activities (129 gallons of gasoline and 3,863 gallons of diesel fuel), the project would provide an energy benefit during long-term operations, reducing diesel fuel usage at the site by approximately 2,190 gallons per year. Therefore, after approximately 22 months of operation under the proposed project, the petroleum-based fuels consumed during construction activities would be completely offset and project would continue reducing fuel usage onsite for the lifetime of the project. Project energy consumption would not be considered wasteful, inefficient, or unnecessary. Therefore, the consumption of fuel and other energy during project construction and operations would have a **less-than-significant impact** on energy resources.

⁵ U.S. Energy Information Administration. Carbon Dioxide Coefficients.
https://www.eia.gov/environment/emissions/co2_vol_mass.php

⁶ U.S. Energy Information Administration. Frequently Asked Questions (FAQs).
<https://www.eia.gov/tools/faqs/faq.php?id=97&t=3>

⁷ U.S. Department of Energy. Energy Efficiency & Renewable Energy. Long-Haul Truck Idling Burns up Profits.
https://afdc.energy.gov/files/u/publication/hdv_idling_2015.pdf

MITIGATION MEASURES ENERGY-1

None required.

IMPACT ENERGY-2

The project would not conflict with or obstruct a state or local plan for renewable energy or energy efficiency. (No Impact)

The Regulatory Setting of this Report describes the regulatory framework for energy usage and conservation at the federal, State, and local level. The project has been reviewed relative to the City of San Leandro 2035 General Plan and 2021 CAP. This analysis finds that the project would not conflict with or obstruct either of these plans because there are no measures applicable to the project. Furthermore, as indicated in Impact ENERGY-1, after approximately 22 months of operation under the proposed project, the petroleum-based fuels consumed during construction activities would be completely offset and the project would continue reducing fuel usage onsite for the lifetime of the project. The project would result in a reduction in GHG emissions and energy usage over the lifetime of the project and would support the intent of the 2021 CAP, which is to reduce GHG emissions in the City of San Leandro. Based on the scale of the project and the fact that the project would reduce energy usage and GHG emissions over the lifetime of the project, the project could not possibly hinder the implementation of energy conservation and renewable energy measures within the 2035 General Plan and 2021 CAP. Therefore, the project would not conflict with or obstruct a state or local plan and the project would have **no impact**.

MITIGATION MEASURES ENERGY-2

None required.

IMPACT ENERGY-3

The project would not require the construction of new or expanded energy production facilities or infrastructure, the construction of which could cause significant environmental impacts. (No Impact)

As stated previously, the project increase of 1,000 kWh per year is negligible, since in 2020 the average annual electricity consumption for a U.S. residential utility customer was approximately 11,000 kWh per year.⁸ Based on the negligible electricity usage and overall reduction in petroleum-based fuels with the project, as identified in Impact ENERGY-1, no expanded energy production facilities would be anticipated, therefore, the project would have **no impact** from the construction of energy production facilities.

MITIGATION MEASURES ENERGY-3

None required.

⁸ U.S. Energy Information Administration. Frequently Asked Questions (FAQs). <https://www.eia.gov/tools/faqs/faq.php?id=97&t=3>

CONCLUSION

The project would require the consumption of petroleum-based fuels during construction and a small amount of electricity during long-term operations. After approximately 22 months of operation under the proposed project, the petroleum-based fuels consumed during construction activities would be completely offset and the project would continue reducing fuel usage onsite for the lifetime of the project. Project energy consumption would not be considered wasteful, inefficient, or unnecessary. The project would not conflict with or obstruct a state or local plan for renewable energy or energy efficiency. The project would not require expanded energy production facilities. All energy impacts would be less than significant or no impact for CEQA purposes.

ATTACHMENTS

ATTACHMENT A – CALEEMOD MODELING OUTPUT AND FUEL CONVERSION CALCULATIONS

ATTACHMENT B – DIESEL FUEL USE REDUCTION FROM REDUCED IDLING

Alco Metals Detailed Report

Table of Contents

1. Basic Project Information
 - 1.1. Basic Project Information
 - 1.2. Land Use Types
 - 1.3. User-Selected Emission Reduction Measures by Emissions Sector
2. Emissions Summary
 - 2.1. Construction Emissions Compared Against Thresholds
 - 2.2. Construction Emissions by Year, Unmitigated
 - 2.4. Operations Emissions Compared Against Thresholds
 - 2.5. Operations Emissions by Sector, Unmitigated
3. Construction Emissions Details
 - 3.1. Demolition Old Wall (2025) - Unmitigated
 - 3.3. Grading New Site (2025) - Unmitigated
 - 3.5. Building New Wall (2025) - Unmitigated
 - 3.7. Building New Scale (2025) - Unmitigated
 - 3.9. Paving New Site/Fixing Pavement (2025) - Unmitigated

4. Operations Emissions Details

4.1. Mobile Emissions by Land Use

4.1.1. Unmitigated

4.2. Energy

4.2.1. Electricity Emissions By Land Use - Unmitigated

4.2.3. Natural Gas Emissions By Land Use - Unmitigated

4.3. Area Emissions by Source

4.3.1. Unmitigated

4.4. Water Emissions by Land Use

4.4.1. Unmitigated

4.5. Waste Emissions by Land Use

4.5.1. Unmitigated

4.6. Refrigerant Emissions by Land Use

4.6.1. Unmitigated

4.7. Offroad Emissions By Equipment Type

4.7.1. Unmitigated

4.8. Stationary Emissions By Equipment Type

4.8.1. Unmitigated

4.9. User Defined Emissions By Equipment Type

4.9.1. Unmitigated

4.10. Soil Carbon Accumulation By Vegetation Type

4.10.1. Soil Carbon Accumulation By Vegetation Type - Unmitigated

4.10.2. Above and Belowground Carbon Accumulation by Land Use Type - Unmitigated

4.10.3. Avoided and Sequestered Emissions by Species - Unmitigated

5. Activity Data

5.1. Construction Schedule

5.2. Off-Road Equipment

5.2.1. Unmitigated

5.3. Construction Vehicles

5.3.1. Unmitigated

5.4. Vehicles

5.4.1. Construction Vehicle Control Strategies

5.5. Architectural Coatings

5.6. Dust Mitigation

5.6.1. Construction Earthmoving Activities

5.6.2. Construction Earthmoving Control Strategies

5.7. Construction Paving

5.8. Construction Electricity Consumption and Emissions Factors

5.9. Operational Mobile Sources

5.9.1. Unmitigated

5.10. Operational Area Sources

5.10.1. Hearths

5.10.1.1. Unmitigated

5.10.2. Architectural Coatings

5.10.3. Landscape Equipment

5.11. Operational Energy Consumption

5.11.1. Unmitigated

5.12. Operational Water and Wastewater Consumption

5.12.1. Unmitigated

5.13. Operational Waste Generation

5.13.1. Unmitigated

5.14. Operational Refrigeration and Air Conditioning Equipment

5.14.1. Unmitigated

5.15. Operational Off-Road Equipment

5.15.1. Unmitigated

5.16. Stationary Sources

5.16.1. Emergency Generators and Fire Pumps

5.16.2. Process Boilers

5.17. User Defined

5.18. Vegetation

5.18.1. Land Use Change

5.18.1.1. Unmitigated

5.18.1. Biomass Cover Type

5.18.1.1. Unmitigated

5.18.2. Sequestration

5.18.2.1. Unmitigated

6. Climate Risk Detailed Report

6.1. Climate Risk Summary

6.2. Initial Climate Risk Scores

6.3. Adjusted Climate Risk Scores

6.4. Climate Risk Reduction Measures

7. Health and Equity Details

7.1. CalEnviroScreen 4.0 Scores

7.2. Healthy Places Index Scores

7.3. Overall Health & Equity Scores

7.4. Health & Equity Measures

7.5. Evaluation Scorecard

7.6. Health & Equity Custom Measures

8. User Changes to Default Data

1. Basic Project Information

1.1. Basic Project Information

Data Field	Value
Project Name	Alco Metals
Construction Start Date	3/1/2025
Operational Year	2026
Lead Agency	—
Land Use Scale	Project/site
Analysis Level for Defaults	County
Windspeed (m/s)	3.90
Precipitation (days)	27.6
Location	37.716573171225704, -122.18808311098752
County	Alameda
City	San Leandro
Air District	Bay Area AQMD
Air Basin	San Francisco Bay Area
TAZ	1409
EDFZ	1
Electric Utility	Pacific Gas & Electric Company
Gas Utility	Pacific Gas & Electric
App Version	2022.1.1.28

1.2. Land Use Types

Land Use Subtype	Size	Unit	Lot Acreage	Building Area (sq ft)	Landscape Area (sq ft)	Special Landscape Area (sq ft)	Population	Description
User Defined Industrial	1.00	User Defined Unit	2.00	0.00	0.00	0.00	—	—

1.3. User-Selected Emission Reduction Measures by Emissions Sector

No measures selected

2. Emissions Summary

2.1. Construction Emissions Compared Against Thresholds

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Un/Mit.	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Unmit.	0.92	0.73	6.47	7.73	0.03	0.21	0.38	0.59	0.20	0.10	0.30	—	3,129	3,129	0.14	0.20	2.84	3,195
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Unmit.	1.07	0.87	7.78	9.62	0.03	0.29	0.61	0.83	0.27	0.10	0.35	—	3,159	3,159	0.14	0.20	0.07	3,209
Average Daily (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Unmit.	0.08	0.06	0.56	0.69	< 0.005	0.02	0.03	0.05	0.02	0.01	0.03	—	240	240	0.01	0.01	0.08	244
Annual (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Unmit.	0.01	0.01	0.10	0.13	< 0.005	< 0.005	0.01	0.01	< 0.005	< 0.005	< 0.005	—	39.7	39.7	< 0.005	< 0.005	0.01	40.4

2.2. Construction Emissions by Year, Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Year	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily - Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
2025	0.92	0.73	6.47	7.73	0.03	0.21	0.38	0.59	0.20	0.10	0.30	—	3,129	3,129	0.14	0.20	2.84	3,195

Daily - Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
2025	1.07	0.87	7.78	9.62	0.03	0.29	0.61	0.83	0.27	0.10	0.35	—	3,159	3,159	0.14	0.20	0.07	3,209
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
2025	0.08	0.06	0.56	0.69	< 0.005	0.02	0.03	0.05	0.02	0.01	0.03	—	240	240	0.01	0.01	0.08	244
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
2025	0.01	0.01	0.10	0.13	< 0.005	< 0.005	0.01	0.01	< 0.005	< 0.005	< 0.005	—	39.7	39.7	< 0.005	< 0.005	0.01	40.4

2.4. Operations Emissions Compared Against Thresholds

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Un/Mit.	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e	
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Unmit.	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.56	0.56	< 0.005	< 0.005	0.00	0.56	
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Unmit.	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.56	0.56	< 0.005	< 0.005	0.00	0.56	
Average Daily (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Unmit.	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.56	0.56	< 0.005	< 0.005	0.00	0.56	
Annual (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Unmit.	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.09	0.09	< 0.005	< 0.005	0.00	0.09	

2.5. Operations Emissions by Sector, Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Sector	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Mobile	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Area	0.00	0.00	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Energy	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	—	0.00	—	0.56	0.56	< 0.005	< 0.005	—	0.56
Water	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Waste	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.56	0.56	< 0.005	< 0.005	0.00	0.56
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Mobile	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Area	0.00	0.00	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Energy	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	—	0.00	—	0.56	0.56	< 0.005	< 0.005	—	0.56
Water	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Waste	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.56	0.56	< 0.005	< 0.005	0.00	0.56
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Mobile	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Area	0.00	0.00	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Energy	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	—	0.00	—	0.56	0.56	< 0.005	< 0.005	—	0.56
Water	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Waste	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.56	0.56	< 0.005	< 0.005	0.00	0.56
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Mobile	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Area	0.00	0.00	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Energy	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	—	0.00	—	0.09	0.09	< 0.005	< 0.005	—	0.09
Water	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Waste	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.09	0.09	< 0.005	< 0.005	0.00	0.09

3. Construction Emissions Details

3.1. Demolition Old Wall (2025) - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Location	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Onsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.66	0.55	3.84	4.87	0.01	0.14	—	0.14	0.13	—	0.13	—	1,622	1,622	0.07	0.01	—	1,628
Demolition	—	—	—	—	—	—	0.00	0.00	—	0.00	0.00	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	< 0.005	< 0.005	0.02	0.03	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	8.89	8.89	< 0.005	< 0.005	—	8.92
Demolition	—	—	—	—	—	—	0.00	0.00	—	0.00	0.00	—	—	—	—	—	—	—

Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	—	1.47	1.47	< 0.005	< 0.005	—	1.48
Demolition	—	—	—	—	—	—	0.00	0.00	—	0.00	0.00	—	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Offsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.03	0.03	0.03	0.34	0.00	0.00	0.08	0.08	0.00	0.02	0.02	—	80.3	80.3	< 0.005	< 0.005	0.01	81.4	
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.08	0.02	1.43	0.55	0.01	0.02	0.30	0.32	0.02	0.08	0.10	—	1,123	1,123	0.06	0.18	0.06	1,178	
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	< 0.005	< 0.005	< 0.005	< 0.005	0.00	0.00	< 0.005	< 0.005	0.00	< 0.005	< 0.005	—	0.44	0.44	< 0.005	< 0.005	< 0.005	0.45	
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	< 0.005	< 0.005	0.01	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	—	6.15	6.15	< 0.005	< 0.005	0.01	6.46	
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	< 0.005	< 0.005	< 0.005	< 0.005	0.00	0.00	< 0.005	< 0.005	0.00	< 0.005	< 0.005	—	0.07	0.07	< 0.005	< 0.005	< 0.005	0.07	
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	—	1.02	1.02	< 0.005	< 0.005	< 0.005	1.07	

3.3. Grading New Site (2025) - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Location	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Onsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.56	0.47	4.16	5.57	0.01	0.21	—	0.21	0.20	—	0.20	—	859	859	0.03	0.01	—	862
Dust From Material Movement	—	—	—	—	—	—	0.53	0.53	—	0.06	0.06	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	< 0.005	< 0.005	0.03	0.05	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	7.06	7.06	< 0.005	< 0.005	—	7.08
Dust From Material Movement	—	—	—	—	—	—	< 0.005	< 0.005	—	< 0.005	< 0.005	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	< 0.005	< 0.005	0.01	0.01	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	1.17	1.17	< 0.005	< 0.005	—	1.17

Dust From Material Movement	—	—	—	—	—	—	< 0.005	< 0.005	—	< 0.005	< 0.005	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Offsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.03	0.03	0.03	0.34	0.00	0.00	0.08	0.08	0.00	0.02	0.02	—	80.3	80.3	< 0.005	< 0.005	0.01	81.4
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	< 0.005	< 0.005	< 0.005	< 0.005	0.00	0.00	< 0.005	< 0.005	0.00	< 0.005	< 0.005	—	0.66	0.66	< 0.005	< 0.005	< 0.005	0.67
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	< 0.005	< 0.005	< 0.005	< 0.005	0.00	0.00	< 0.005	< 0.005	0.00	< 0.005	< 0.005	—	0.11	0.11	< 0.005	< 0.005	< 0.005	0.11
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00

3.5. Building New Wall (2025) - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Location	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Onsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.80	0.67	5.09	6.80	0.02	0.19	—	0.19	0.17	—	0.17	—	1,921	1,921	0.08	0.02	—	1,927
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.80	0.67	5.09	6.80	0.02	0.19	—	0.19	0.17	—	0.17	—	1,921	1,921	0.08	0.02	—	1,927
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.02	0.02	0.14	0.19	< 0.005	0.01	—	0.01	< 0.005	—	< 0.005	—	52.6	52.6	< 0.005	< 0.005	—	52.8
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	< 0.005	< 0.005	0.03	0.03	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	8.71	8.71	< 0.005	< 0.005	—	8.74
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Offsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Worker	0.03	0.03	0.02	0.38	0.00	0.00	0.08	0.08	0.00	0.02	0.02	—	86.6	86.6	< 0.005	< 0.005	0.34	87.9
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.09	0.03	1.36	0.54	0.01	0.02	0.30	0.32	0.02	0.08	0.10	—	1,122	1,122	0.06	0.18	2.49	1,180
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.03	0.03	0.03	0.34	0.00	0.00	0.08	0.08	0.00	0.02	0.02	—	80.3	80.3	< 0.005	< 0.005	0.01	81.4
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.08	0.02	1.43	0.55	0.01	0.02	0.30	0.32	0.02	0.08	0.10	—	1,123	1,123	0.06	0.18	0.06	1,178
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	< 0.005	< 0.005	< 0.005	0.01	0.00	0.00	< 0.005	< 0.005	0.00	< 0.005	< 0.005	—	2.22	2.22	< 0.005	< 0.005	< 0.005	2.25
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	< 0.005	< 0.005	0.04	0.01	< 0.005	< 0.005	0.01	0.01	< 0.005	< 0.005	< 0.005	—	30.8	30.8	< 0.005	< 0.005	0.03	32.3
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	< 0.005	< 0.005	< 0.005	< 0.005	0.00	0.00	< 0.005	< 0.005	0.00	< 0.005	< 0.005	—	0.37	0.37	< 0.005	< 0.005	< 0.005	0.37
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	< 0.005	< 0.005	0.01	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	—	5.09	5.09	< 0.005	< 0.005	< 0.005	5.35

3.7. Building New Scale (2025) - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Location	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Onsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.09	0.08	0.74	1.04	< 0.005	0.04	—	0.04	0.04	—	0.04	—	152	152	0.01	< 0.005	—	153

Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	0.42	0.42	< 0.005	< 0.005	—	0.42	
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	0.07	0.07	< 0.005	< 0.005	—	0.07	
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Offsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.03	0.03	0.02	0.38	0.00	0.00	0.08	0.08	0.00	0.02	0.02	—	86.6	86.6	< 0.005	< 0.005	0.34	87.9	
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.01	< 0.005	0.17	0.07	< 0.005	< 0.005	0.04	0.04	< 0.005	0.01	0.01	—	140	140	0.01	0.02	0.31	148	
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	< 0.005	< 0.005	< 0.005	< 0.005	0.00	0.00	< 0.005	< 0.005	0.00	< 0.005	< 0.005	—	0.22	0.22	< 0.005	< 0.005	< 0.005	0.22	
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	—	0.38	0.38	< 0.005	< 0.005	< 0.005	0.40	

Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	< 0.005	< 0.005	< 0.005	< 0.005	0.00	0.00	< 0.005	< 0.005	0.00	< 0.005	< 0.005	—	0.04	0.04	< 0.005	< 0.005	< 0.005	0.04
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	—	0.06	0.06	< 0.005	< 0.005	< 0.005	0.07

3.9. Paving New Site/Fixing Pavement (2025) - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Location	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Onsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.97	0.82	6.68	8.87	0.02	0.27	—	0.27	0.25	—	0.25	—	2,237	2,237	0.09	0.02	—	2,244
Paving	0.00	0.00	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.04	0.03	0.27	0.36	< 0.005	0.01	—	0.01	0.01	—	0.01	—	91.9	91.9	< 0.005	< 0.005	—	92.2
Paving	0.00	0.00	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Off-Road	0.01	0.01	0.05	0.07	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	15.2	15.2	< 0.005	< 0.005	—	15.3
Paving	0.00	0.00	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Offsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.03	0.03	0.03	0.34	0.00	0.00	0.08	0.08	0.00	0.02	0.02	—	80.3	80.3	< 0.005	< 0.005	0.01	81.4
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.06	0.02	1.07	0.41	0.01	0.02	0.22	0.24	0.02	0.06	0.08	—	842	842	0.04	0.14	0.05	884
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	< 0.005	< 0.005	< 0.005	0.01	0.00	0.00	< 0.005	< 0.005	0.00	< 0.005	< 0.005	—	3.32	3.32	< 0.005	< 0.005	0.01	3.37
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	< 0.005	< 0.005	0.04	0.02	< 0.005	< 0.005	0.01	0.01	< 0.005	< 0.005	< 0.005	—	34.6	34.6	< 0.005	0.01	0.03	36.3
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	< 0.005	< 0.005	< 0.005	< 0.005	0.00	0.00	< 0.005	< 0.005	0.00	< 0.005	< 0.005	—	0.55	0.55	< 0.005	< 0.005	< 0.005	0.56
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	< 0.005	< 0.005	0.01	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	—	5.73	5.73	< 0.005	< 0.005	0.01	6.02

4. Operations Emissions Details

4.1. Mobile Emissions by Land Use

4.1.1. Unmitigated

Mobile source emissions results are presented in Sections 2.6. No further detailed breakdown of emissions is available.

4.2. Energy

4.2.1. Electricity Emissions By Land Use - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Land Use	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
User Defined Industrial	—	—	—	—	—	—	—	—	—	—	—	—	0.56	0.56	< 0.005	< 0.005	—	0.56
Total	—	—	—	—	—	—	—	—	—	—	—	—	0.56	0.56	< 0.005	< 0.005	—	0.56
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
User Defined Industrial	—	—	—	—	—	—	—	—	—	—	—	—	0.56	0.56	< 0.005	< 0.005	—	0.56
Total	—	—	—	—	—	—	—	—	—	—	—	—	0.56	0.56	< 0.005	< 0.005	—	0.56
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
User Defined Industrial	—	—	—	—	—	—	—	—	—	—	—	—	0.09	0.09	< 0.005	< 0.005	—	0.09
Total	—	—	—	—	—	—	—	—	—	—	—	—	0.09	0.09	< 0.005	< 0.005	—	0.09

4.2.3. Natural Gas Emissions By Land Use - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Land Use	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

User Defined Industrial	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	—	0.00	—	0.00	0.00	0.00	0.00	—	0.00
Total	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	—	0.00	—	0.00	0.00	0.00	0.00	—	0.00
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
User Defined Industrial	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	—	0.00	—	0.00	0.00	0.00	0.00	—	0.00
Total	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	—	0.00	—	0.00	0.00	0.00	0.00	—	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
User Defined Industrial	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	—	0.00	—	0.00	0.00	0.00	0.00	—	0.00
Total	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	—	0.00	—	0.00	0.00	0.00	0.00	—	0.00

4.3. Area Emissions by Source

4.3.1. Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Source	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Consumer Products	0.00	0.00	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Architectural Coatings	0.00	0.00	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	0.00	0.00	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Consumer Products	0.00	0.00	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Architectural Coatings	0.00	0.00	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	0.00	0.00	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Consumer Products	0.00	0.00	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Architectural Coatings	0.00	0.00	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	0.00	0.00	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

4.4. Water Emissions by Land Use

4.4.1. Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Land Use	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
User Defined Industrial	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00

Total	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
User Defined Industrial	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Total	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
User Defined Industrial	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Total	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00

4.5. Waste Emissions by Land Use

4.5.1. Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Land Use	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
User Defined Industrial	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Total	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
User Defined Industrial	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Total	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00

Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
User Defined Industrial	—	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Total	—	—	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00

4.6. Refrigerant Emissions by Land Use

4.6.1. Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Land Use	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

4.7. Offroad Emissions By Equipment Type

4.7.1. Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Equipm ent Type	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

4.8. Stationary Emissions By Equipment Type

4.8.1. Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Equipm ent Type	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

4.9. User Defined Emissions By Equipment Type

4.9.1. Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Equipm ent Type	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

4.10. Soil Carbon Accumulation By Vegetation Type

4.10.1. Soil Carbon Accumulation By Vegetation Type - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Vegetati on	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

4.10.2. Above and Belowground Carbon Accumulation by Land Use Type - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Land Use	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

4.10.3. Avoided and Sequestered Emissions by Species - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Species	TOG	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Avoided	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Sequestered	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Removed	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Avoided	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Sequestered	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Removed	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Avoided	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Sequestered	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Removed	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

5. Activity Data

5.1. Construction Schedule

Phase Name	Phase Type	Start Date	End Date	Days Per Week	Work Days per Phase	Phase Description
Demolition Old Wall	Demolition	3/27/2025	3/28/2025	5.00	2.00	—
Grading New Site	Grading	3/1/2025	3/5/2025	5.00	3.00	—
Building New Wall	Building Construction	3/29/2025	4/11/2025	5.00	10.0	—
Building New Scale	Building Construction	4/12/2025	4/14/2025	5.00	1.00	—
Paving New Site/Fixing Pavement	Paving	3/6/2025	3/26/2025	5.00	15.0	—

5.2. Off-Road Equipment

5.2.1. Unmitigated

Phase Name	Equipment Type	Fuel Type	Engine Tier	Number per Day	Hours Per Day	Horsepower	Load Factor
Demolition Old Wall	Tractors/Loaders/Back hoes	Diesel	Average	1.00	8.00	84.0	0.37
Demolition Old Wall	Off-Highway Trucks	Diesel	Average	1.00	8.00	376	0.38
Grading New Site	Tractors/Loaders/Back hoes	Diesel	Average	1.00	8.00	84.0	0.37
Grading New Site	Graders	Diesel	Average	1.00	8.00	148	0.41
Building New Wall	Tractors/Loaders/Back hoes	Diesel	Average	1.00	8.00	84.0	0.37
Building New Wall	Off-Highway Trucks	Diesel	Average	1.00	8.00	376	0.38
Building New Wall	Paving Equipment	Diesel	Average	1.00	8.00	89.0	0.36
Building New Scale	Forklifts	Diesel	Average	1.00	8.00	82.0	0.20
Paving New Site/Fixing Pavement	Tractors/Loaders/Back hoes	Diesel	Average	1.00	8.00	84.0	0.37
Paving New Site/Fixing Pavement	Pavers	Diesel	Average	1.00	8.00	81.0	0.42
Paving New Site/Fixing Pavement	Paving Equipment	Diesel	Average	1.00	8.00	89.0	0.36
Paving New Site/Fixing Pavement	Off-Highway Trucks	Diesel	Average	1.00	8.00	376	0.38

5.3. Construction Vehicles

5.3.1. Unmitigated

Phase Name	Trip Type	One-Way Trips per Day	Miles per Trip	Vehicle Mix
Grading New Site	—	—	—	—
Grading New Site	Worker	10.0	11.7	LDA,LDT1,LDT2

Grading New Site	Vendor	—	8.40	HHDT,MHDT
Grading New Site	Hauling	0.00	20.0	HHDT
Grading New Site	Onsite truck	—	—	HHDT
Demolition Old Wall	—	—	—	—
Demolition Old Wall	Worker	10.0	11.7	LDA,LDT1,LDT2
Demolition Old Wall	Vendor	—	8.40	HHDT,MHDT
Demolition Old Wall	Hauling	16.0	20.0	HHDT
Demolition Old Wall	Onsite truck	—	—	HHDT
Building New Wall	—	—	—	—
Building New Wall	Worker	10.0	11.7	LDA,LDT1,LDT2
Building New Wall	Vendor	0.00	8.40	HHDT,MHDT
Building New Wall	Hauling	16.0	20.0	HHDT
Building New Wall	Onsite truck	—	—	HHDT
Paving New Site/Fixing Pavement	—	—	—	—
Paving New Site/Fixing Pavement	Worker	10.0	11.7	LDA,LDT1,LDT2
Paving New Site/Fixing Pavement	Vendor	—	8.40	HHDT,MHDT
Paving New Site/Fixing Pavement	Hauling	12.0	20.0	HHDT
Paving New Site/Fixing Pavement	Onsite truck	—	—	HHDT
Building New Scale	—	—	—	—
Building New Scale	Worker	10.0	11.7	LDA,LDT1,LDT2
Building New Scale	Vendor	0.00	8.40	HHDT,MHDT
Building New Scale	Hauling	2.00	20.0	HHDT
Building New Scale	Onsite truck	—	—	HHDT

5.4. Vehicles

5.4.1. Construction Vehicle Control Strategies

Non-applicable. No control strategies activated by user.

5.5. Architectural Coatings

Phase Name	Residential Interior Area Coated (sq ft)	Residential Exterior Area Coated (sq ft)	Non-Residential Interior Area Coated (sq ft)	Non-Residential Exterior Area Coated (sq ft)	Parking Area Coated (sq ft)
------------	--	--	--	--	-----------------------------

5.6. Dust Mitigation

5.6.1. Construction Earthmoving Activities

Phase Name	Material Imported (cy)	Material Exported (cy)	Acres Graded (acres)	Material Demolished (sq. ft.)	Acres Paved (acres)
Demolition Old Wall	0.00	0.00	0.00	—	—
Grading New Site	—	—	2.00	0.00	—
Paving New Site/Fixing Pavement	0.00	0.00	0.00	0.00	2.00

5.6.2. Construction Earthmoving Control Strategies

Non-applicable. No control strategies activated by user.

5.7. Construction Paving

Land Use	Area Paved (acres)	% Asphalt
User Defined Industrial	2.00	0%

5.8. Construction Electricity Consumption and Emissions Factors

kWh per Year and Emission Factor (lb/MWh)

Year	kWh per Year	CO2	CH4	N2O
2025	0.00	204	0.03	< 0.005

5.9. Operational Mobile Sources

5.9.1. Unmitigated

Land Use Type	Trips/Weekday	Trips/Saturday	Trips/Sunday	Trips/Year	VM/Weekday	VM/Saturday	VM/Sunday	VM/Year
Total all Land Uses	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

5.10. Operational Area Sources

5.10.1. Hearths

5.10.1.1. Unmitigated

5.10.2. Architectural Coatings

Residential Interior Area Coated (sq ft)	Residential Exterior Area Coated (sq ft)	Non-Residential Interior Area Coated (sq ft)	Non-Residential Exterior Area Coated (sq ft)	Parking Area Coated (sq ft)
0	0.00	0.00	0.00	—

5.10.3. Landscape Equipment

Equipment Type	Fuel Type	Number Per Day	Hours per Day	Hours per Year	Horsepower	Load Factor
----------------	-----------	----------------	---------------	----------------	------------	-------------

5.11. Operational Energy Consumption

5.11.1. Unmitigated

Electricity (kWh/yr) and CO₂ and CH₄ and N₂O and Natural Gas (kBtu/yr)

Land Use	Electricity (kWh/yr)	CO ₂	CH ₄	N ₂ O	Natural Gas (kBtu/yr)
User Defined Industrial	1,000	204	0.0330	0.0040	0.00

5.12. Operational Water and Wastewater Consumption

5.12.1. Unmitigated

Land Use	Indoor Water (gal/year)	Outdoor Water (gal/year)
User Defined Industrial	0.00	0.00

5.13. Operational Waste Generation

5.13.1. Unmitigated

Land Use	Waste (ton/year)	Cogeneration (kWh/year)
User Defined Industrial	0.00	—

5.14. Operational Refrigeration and Air Conditioning Equipment

5.14.1. Unmitigated

Land Use Type	Equipment Type	Refrigerant	GWP	Quantity (kg)	Operations Leak Rate	Service Leak Rate	Times Serviced
---------------	----------------	-------------	-----	---------------	----------------------	-------------------	----------------

5.15. Operational Off-Road Equipment

5.15.1. Unmitigated

Equipment Type	Fuel Type	Engine Tier	Number per Day	Hours Per Day	Horsepower	Load Factor
----------------	-----------	-------------	----------------	---------------	------------	-------------

5.16. Stationary Sources

5.16.1. Emergency Generators and Fire Pumps

Equipment Type	Fuel Type	Number per Day	Hours per Day	Hours per Year	Horsepower	Load Factor
----------------	-----------	----------------	---------------	----------------	------------	-------------

5.16.2. Process Boilers

Equipment Type	Fuel Type	Number	Boiler Rating (MMBtu/hr)	Daily Heat Input (MMBtu/day)	Annual Heat Input (MMBtu/yr)
----------------	-----------	--------	--------------------------	------------------------------	------------------------------

5.17. User Defined

Equipment Type	Fuel Type
----------------	-----------

5.18. Vegetation

5.18.1. Land Use Change

5.18.1.1. Unmitigated

Vegetation Land Use Type	Vegetation Soil Type	Initial Acres	Final Acres
--------------------------	----------------------	---------------	-------------

5.18.1. Biomass Cover Type

5.18.1.1. Unmitigated

Biomass Cover Type	Initial Acres	Final Acres
--------------------	---------------	-------------

5.18.2. Sequestration

5.18.2.1. Unmitigated

Tree Type	Number	Electricity Saved (kWh/year)	Natural Gas Saved (btu/year)
-----------	--------	------------------------------	------------------------------

6. Climate Risk Detailed Report

6.1. Climate Risk Summary

Cal-Adapt midcentury 2040–2059 average projections for four hazards are reported below for your project location. These are under Representation Concentration Pathway (RCP) 8.5 which assumes GHG emissions will continue to rise strongly through 2050 and then plateau around 2100.

Climate Hazard	Result for Project Location	Unit
Temperature and Extreme Heat	7.80	annual days of extreme heat
Extreme Precipitation	5.35	annual days with precipitation above 20 mm
Sea Level Rise	—	meters of inundation depth
Wildfire	0.00	annual hectares burned

Temperature and Extreme Heat data are for grid cell in which your project are located. The projection is based on the 98th historical percentile of daily maximum/minimum temperatures from observed historical data (32 climate model ensemble from Cal-Adapt, 2040–2059 average under RCP 8.5). Each grid cell is 6 kilometers (km) by 6 km, or 3.7 miles (mi) by 3.7 mi.

Extreme Precipitation data are for the grid cell in which your project are located. The threshold of 20 mm is equivalent to about $\frac{3}{4}$ an inch of rain, which would be light to moderate rainfall if received over a full day or heavy rain if received over a period of 2 to 4 hours. Each grid cell is 6 kilometers (km) by 6 km, or 3.7 miles (mi) by 3.7 mi.

Sea Level Rise data are for the grid cell in which your project are located. The projections are from Radke et al. (2017), as reported in Cal-Adapt (Radke et al., 2017, CEC-500-2017-008), and consider inundation location and depth for the San Francisco Bay, the Sacramento-San Joaquin River Delta and California coast resulting different increments of sea level rise coupled with extreme storm events. Users may select from four scenarios to view the range in potential inundation depth for the grid cell. The four scenarios are: No rise, 0.5 meter, 1.0 meter, 1.41 meters

Wildfire data are for the grid cell in which your project are located. The projections are from UC Davis, as reported in Cal-Adapt (2040–2059 average under RCP 8.5), and consider historical data of climate, vegetation, population density, and large (> 400 ha) fire history. Users may select from four model simulations to view the range in potential wildfire probabilities for the grid cell. The four simulations make different assumptions about expected rainfall and temperature are: Warmer/drier (HadGEM2-ES), Cooler/wetter (CNRM-CM5), Average conditions (CanESM2), Range of different rainfall and temperature possibilities (MIROC5). Each grid cell is 6 kilometers (km) by 6 km, or 3.7 miles (mi) by 3.7 mi.

6.2. Initial Climate Risk Scores

Climate Hazard	Exposure Score	Sensitivity Score	Adaptive Capacity Score	Vulnerability Score
Temperature and Extreme Heat	N/A	N/A	N/A	N/A
Extreme Precipitation	2	0	0	N/A
Sea Level Rise	1	0	0	N/A
Wildfire	1	0	0	N/A
Flooding	N/A	N/A	N/A	N/A
Drought	N/A	N/A	N/A	N/A
Snowpack Reduction	N/A	N/A	N/A	N/A
Air Quality Degradation	0	0	0	N/A

The sensitivity score reflects the extent to which a project would be adversely affected by exposure to a climate hazard. Exposure is rated on a scale of 1 to 5, with a score of 5 representing the greatest exposure.

The adaptive capacity of a project refers to its ability to manage and reduce vulnerabilities from projected climate hazards. Adaptive capacity is rated on a scale of 1 to 5, with a score of 5 representing the greatest ability to adapt.

The overall vulnerability scores are calculated based on the potential impacts and adaptive capacity assessments for each hazard. Scores do not include implementation of climate risk reduction measures.

6.3. Adjusted Climate Risk Scores

Climate Hazard	Exposure Score	Sensitivity Score	Adaptive Capacity Score	Vulnerability Score
Temperature and Extreme Heat	N/A	N/A	N/A	N/A
Extreme Precipitation	2	1	1	3
Sea Level Rise	1	1	1	2

Wildfire	1	1	1	2
Flooding	N/A	N/A	N/A	N/A
Drought	N/A	N/A	N/A	N/A
Snowpack Reduction	N/A	N/A	N/A	N/A
Air Quality Degradation	1	1	1	2

The sensitivity score reflects the extent to which a project would be adversely affected by exposure to a climate hazard. Exposure is rated on a scale of 1 to 5, with a score of 5 representing the greatest exposure.

The adaptive capacity of a project refers to its ability to manage and reduce vulnerabilities from projected climate hazards. Adaptive capacity is rated on a scale of 1 to 5, with a score of 5 representing the greatest ability to adapt.

The overall vulnerability scores are calculated based on the potential impacts and adaptive capacity assessments for each hazard. Scores include implementation of climate risk reduction measures.

6.4. Climate Risk Reduction Measures

7. Health and Equity Details

7.1. CalEnviroScreen 4.0 Scores

The maximum CalEnviroScreen score is 100. A high score (i.e., greater than 50) reflects a higher pollution burden compared to other census tracts in the state.

Indicator	Result for Project Census Tract
Exposure Indicators	—
AQ-Ozone	6.38
AQ-PM	27.0
AQ-DPM	93.5
Drinking Water	4.21
Lead Risk Housing	80.9
Pesticides	0.00
Toxic Releases	61.7
Traffic	84.0
Effect Indicators	—
CleanUp Sites	90.4
Groundwater	97.4

Haz Waste Facilities/Generators	94.1
Impaired Water Bodies	87.0
Solid Waste	99.0
Sensitive Population	—
Asthma	82.1
Cardio-vascular	58.3
Low Birth Weights	89.3
Socioeconomic Factor Indicators	—
Education	65.7
Housing	52.1
Linguistic	56.9
Poverty	49.1
Unemployment	28.2

7.2. Healthy Places Index Scores

The maximum Health Places Index score is 100. A high score (i.e., greater than 50) reflects healthier community conditions compared to other census tracts in the state.

Indicator	Result for Project Census Tract
Economic	—
Above Poverty	41.71692545
Employed	41.16514821
Median HI	38.4832542
Education	—
Bachelor's or higher	37.61067625
High school enrollment	100
Preschool enrollment	50.42987296
Transportation	—
Auto Access	43.30809701
Active commuting	81.6501989

Social	—
2-parent households	22.43038624
Voting	50.46836905
Neighborhood	—
Alcohol availability	30.15526755
Park access	46.99088926
Retail density	81.49621455
Supermarket access	65.50750674
Tree canopy	46.49044014
Housing	—
Homeownership	29.00038496
Housing habitability	56.17862184
Low-inc homeowner severe housing cost burden	47.44001027
Low-inc renter severe housing cost burden	73.84832542
Uncrowded housing	41.35762864
Health Outcomes	—
Insured adults	27.75567817
Arthritis	32.0
Asthma ER Admissions	19.0
High Blood Pressure	58.0
Cancer (excluding skin)	47.4
Asthma	46.1
Coronary Heart Disease	40.3
Chronic Obstructive Pulmonary Disease	37.6
Diagnosed Diabetes	34.4
Life Expectancy at Birth	47.0
Cognitively Disabled	33.5
Physically Disabled	57.4

Heart Attack ER Admissions	33.6
Mental Health Not Good	43.4
Chronic Kidney Disease	35.4
Obesity	53.5
Pedestrian Injuries	19.6
Physical Health Not Good	39.2
Stroke	34.3
Health Risk Behaviors	—
Binge Drinking	81.4
Current Smoker	41.5
No Leisure Time for Physical Activity	34.1
Climate Change Exposures	—
Wildfire Risk	0.0
SLR Inundation Area	21.2
Children	81.0
Elderly	59.3
English Speaking	28.9
Foreign-born	76.0
Outdoor Workers	44.4
Climate Change Adaptive Capacity	—
Impervious Surface Cover	36.8
Traffic Density	91.9
Traffic Access	23.0
Other Indices	—
Hardship	62.4
Other Decision Support	—
2016 Voting	30.1

7.3. Overall Health & Equity Scores

Metric	Result for Project Census Tract
CalEnviroScreen 4.0 Score for Project Location (a)	87.0
Healthy Places Index Score for Project Location (b)	48.0
Project Located in a Designated Disadvantaged Community (Senate Bill 535)	Yes
Project Located in a Low-Income Community (Assembly Bill 1550)	Yes
Project Located in a Community Air Protection Program Community (Assembly Bill 617)	No

a: The maximum CalEnviroScreen score is 100. A high score (i.e., greater than 50) reflects a higher pollution burden compared to other census tracts in the state.

b: The maximum Health Places Index score is 100. A high score (i.e., greater than 50) reflects healthier community conditions compared to other census tracts in the state.

7.4. Health & Equity Measures

No Health & Equity Measures selected.

7.5. Evaluation Scorecard

Health & Equity Evaluation Scorecard not completed.

7.6. Health & Equity Custom Measures

No Health & Equity Custom Measures created.

8. User Changes to Default Data

Screen	Justification
Characteristics: Project Details	Project is in a highly urban area
Land Use	Approximately 2 acre site plus addition of one new scale
Construction: Construction Phases	Per Applicant Data Request Response
Construction: Off-Road Equipment	Per Applicant Data Request Response
Construction: Dust From Material Movement	Per Applicant Data Request Response
Construction: Trips and VMT	Per Applicant Data Request Response
Construction: Paving	Per Applicant Data Request Response
Operations: Energy Use	Per Applicant Data Request Response, 1,000 kwh annually for new scale

Construction Fuel Usage

39.25 MT CO ₂	1.15 MT CO ₂
10.16 kg/CO ₂ /gal	8.89 kg/CO ₂ /gal
3,863 gals Diesel	129 gals Gas

Source: U.S. Energy Information Administration, Carbon Dioxide Emissions Coefficients, February 2, 2016. https://www.eia.gov/environment/emissions/co2_vol_mass.php

Carbon Dioxide Emissions Coefficients by Fuel

Carbon Dioxide (CO ₂) Factors:	Pounds CO ₂	Kilograms CO ₂	Pounds CO ₂	Kilograms CO ₂
	Per Unit of Volume or Mass	Volume or Mass	Million Btu	Million Btu
For homes and businesses				
Propane	12.70/gallon	5.76/gallon	139.05	63.07
Butane	14.80/gallon	6.71/gallon	143.20	64.95
Butane/Propane Mix	13.70/gallon	6.21/gallon	141.12	64.01
Home Heating and Diesel Fuel (Distillate)	22.40/gallon	10.16/gallon	161.30	73.16
Kerosene	21.50/gallon	9.75/gallon	159.40	72.30
Coal (All types)	4,631.50/short ton	2,100.82/short ton	210.20	95.35
Natural Gas	117.10/thousand cubic feet	53.12/thousand cubic feet	117.00	53.07
Gasoline	19.60/gallon	8.89/gallon	157.20	71.30
Residual Heating Fuel (Businesses only)	26.00/gallon	11.79/gallon	173.70	78.79
Other transportation fuels				
Jet Fuel	21.10/gallon	9.57/gallon	156.30	70.90
Aviation Gas	18.40/gallon	8.35/gallon	152.60	69.20

Attachment B -- DIESEL FUEL USE REDUCTION FROM REDUCED IDLING

	Project Idling Fuel Reduction			
	Existing Baseline	Project	Project Reduction	
Average Vehicles Per Day		90	90	
Idling Estimate Per Vehicle		10	5	
Fuel Consumption (gal/idling hour)		0.8	0.8	
Total Daily Fuel Consumption		12	6	6 gallons per day
Total Annual Fuel Consumption		4380	2190	2190 gallons per year